

Start Flood Flat IP65 5000LM 865 Black
0050154



Features

• The streamlined, durable, lightweight die-cast aluminium body makes Start Flood Flat a perfect choice for building facades, car parks, garages and construction areas. The product includes 1 m pre-wired stripped cable and fitting bracket for quick and easy installation and the universal mounting bracket allows wall or surface mounting with the possibility of vertical tilting. Black (RAL9017) housing, white reflector, 5000 lm, 45 W, 111 lm/W, 6500K, non dimmable, CRI>80, IP65, IK06, Class I, lifespan L70:B50: 90000 hrs, 151 x 190 x 30 mm (L x W x H). Weight: 0.74kg.


Product Overview

Product name	Start Flood Flat IP65 5000LM 865 Black
Technology	LED
General application	Residential & Consumer
ETIM Class	EC001744
Fixture luminous flux (lm)	5000
Luminaire efficacy (lm/W)	111
Colour temperature (K)	6500
Light colour	Cool White
CRI (Ra)	80
Colour Variation Initial (SDCM)	5
Beam Angle (°)	110
Photobiological Risk Group	RG1
Total power consumption (W)	45
Electrical protection	Class I
Dimmable	No
LED Flickering Rate	Low (6% - 20%)
Housing colour	Black
IP rating	IP65

**Start Flood Flat IP65 5000LM 865 Black
0050154**

IK rating	IK06
Product EAN number	5410288501543
Warranty	3 years
Dimming method	N/A

Photometry



Technical drawings

