

START eco Downlight 5in1 50-125 1150LM
0053413



Features

- START eco Downlight 5in1 is an integrated LED recessed / surface mounted downlight with built in non dimmable driver. Colour temperature (3000K, 4000K and 6500K) can be adjusted by a 3-way switch located on the back of the fixture. Adaptability to various cut-outs from 50mm to 125mm. 11W, 1150lm, 105lm/W.


Product Overview

Product name	START eco Downlight 5in1 50-125 1150LM
Technology	LED
Housing	PC Polycarbonate
Mount	Ceiling recessed mounting
General application	Residential & Consumer
ETIM Class	EC001744
E-number FI	4278100
Fixture luminous flux (lm)	1150
Luminaire efficacy (lm/W)	105
Colour temperature (K)	4000
CRI (Ra)	80
Colour Variation Initial (SDCM)	6
Beam Angle (°)	110
Glare control	< 23
Photobiological Risk Group	RG0
Total power consumption (W)	11
Electrical protection	Class II
Control gear type	LED driver constant current
Dimmable	No
LED Flickering Rate	Ultra low (5% or less)
Housing colour	RAL 9003 - Signal white

START eco Downlight 5in1 50-125 1150LM 0053413

IP rating	IP20
IK rating	IK03
Product EAN number	5410288534138
Warranty	3 years

Photometry



Technical drawings

