


START Waterproof Single 1200 IP65 EM 2800lm 840
0067953



Features

- Start Waterproof, integrated LED weatherproof luminaire, with UV stabilized flat diffuser and linear prisms designed to achieve uniform lit appearance, optimise light output and to reduce glare, 301 stainless steel diffuser clips and fixing brackets for surface mounting. Polycarbonate housing, Polycarbonate diffuser, 2750 lm, 24 W, 115 lm/W, 4000 K, drive current 350 mA, Non dimmable, 3 hours emergency, CRI80, IP65, IK08, Class I, nominal average life (h):50000, 1278 mm x 84 mm x 75 mm ,energy class: A++ A+ A, D-mark


Product Overview

Product name	START Waterproof Single 1200 IP65 EM 2800lm 840
Technology	LED
Housing	PC Polycarbonate
Fixture rating	Enclosed
General application	Logistics & Industry
ETIM Class	EC002892
E-number FI	4309052
Fixture luminous flux (lm)	2750
Luminaire efficacy (lm/W)	115
Colour temperature (K)	4000
Light colour	Neutral White
CRI (Ra)	80
Glare control	< 26
Photobiological Risk Group	RG0
Total power consumption (W)	24
Electrical protection	Class I
Dimmable	No
Housing colour	Grey

START Waterproof Single 1200 IP65 EM 2800lm 840
0067953

IP rating	IP65
IK rating	IK08
Product EAN number	5410288679532
Warranty	5 years
Dimming method	N/A

Photometry



Technical drawings

