

### Features

- 600mm diameter circular architectural luminaire, can be surface mounted or suspended. Powder coated aluminium housing (RAL9016) with polycarbonate opal diffuser. Direct/indirect (halo) light distribution, 5190lm luminous flux, 41.5W system power, 125lm/W luminaire efficacy. Constant current driver. 3 hours integrated emergency. Colour rendering index Ra >80, 3000K Warm White LED, chromaticity tolerance of 3-step MacAdam ellipse. IP40, IK03. 450mA drive current. Electrical protection Class I, 220-240V. Reported lifetime 66k hours L90B10.

### Product Overview


|                                 |                                          |
|---------------------------------|------------------------------------------|
| Product name                    | COLOSSAL 600mm 830 OPAL DIR+HAL WHITE EM |
| Technology                      | LED (3 SDCM)                             |
| Cap/Base                        | N/A                                      |
| Housing                         | Aluminium                                |
| Mount                           | Suspended                                |
| General application             | Hospitality, Office                      |
| ETIM Class                      | EC002892                                 |
| Fixture luminous flux (lm)      | 5190                                     |
| Luminous flux (lm)              | 5190                                     |
| Luminaire efficacy (lm/W)       | 125                                      |
| Colour temperature (K)          | 3000                                     |
| Light colour                    | Warm White                               |
| CRI (Ra)                        | 80                                       |
| Colour Variation Initial (SDCM) | 3                                        |
| Glare control                   | < 22                                     |
| Photobiological Risk Group      | RG0                                      |
| Total power consumption (W)     | 41.5                                     |
| Electrical protection           | Class I                                  |

# Concord

## COLOSSAL 600mm 830 OPAL DIR+HAL WHITE EM 2071198

|                     |                                  |
|---------------------|----------------------------------|
| Control gear type   | LED driver constant current      |
| Dimmable            | No                               |
| LED Flickering Rate | Ultra low (5% or less)           |
| Housing colour      | RAL 9016 - Traffic white / Bezel |
| IP rating           | IP40/20                          |
| IK rating           | IK07                             |
| Product EAN number  | 5025768711987                    |
| Warranty            | 5 years                          |
| Colour Code         | 830                              |
| Dimming method      | N/A                              |

### Photometry



### Technical drawings

