

COLOSSAL 600mm 830 OPAL DIR+HAL WHITE DALI 2071199



Features

- 600mm diameter circular architectural luminaire, can be surface mounted or suspended. Powder coated aluminium housing (RAL9016) with polycarbonate opal diffuser. Direct/indirect (halo) light distribution, 5190lm luminous flux, 40.1W system power, 129lm/W luminaire efficacy. DALI dimmable. Colour rendering index Ra >80, 3000K Warm White LED, chromaticity tolerance of 3-step MacAdam ellipse. IP40, IK03. 450mA drive current. Electrical protection Class I, 220-240V. Reported lifetime 66k hours L90B10.

Product Overview


Product name	COLOSSAL 600mm 830 OPAL DIR+HAL WHITE DALI
Technology	LED (3 SDCM)
Cap/Base	N/A
Housing	Aluminium
Mount	Suspended
General application	Hospitality, Office
ETIM Class	EC002892
Fixture luminous flux (lm)	5190
Luminous flux (lm)	5190
Luminaire efficacy (lm/W)	129
Colour temperature (K)	3000
Light colour	Warm White
CRI (Ra)	80
Colour Variation Initial (SDCM)	3
Glare control	< 22
Photobiological Risk Group	RG0
Total power consumption (W)	40.1
Electrical protection	Class I
Control gear type	Other
Dimmable	Yes

Concord

COLOSSAL 600mm 830 OPAL DIR+HAL WHITE DALI 2071199

LED Flickering Rate	Ultra low (5% or less)
Housing colour	RAL 9016 - Traffic white / Bezel
IP rating	IP40/20
IK rating	IK07
Product EAN number	5025768711994
Warranty	5 years
Colour Code	830
Dimming method	DALI-2

Photometry



Technical drawings

