


CONNECT AND PROTECT

Junction box

PRODUCT OVERVIEW



The nVent RAYCHEM JB-82 is a standard, non-hazardous polycarbonate junction box.


It may be used to make a power connection, splice, powered splice, powered tee or simple tee, for use with nVent RAYCHEM industrial parallel heating cables.

Up to four heating cables or three heating cables and the appropriate size power cable can be accommodated through the four entries and connected to the rail mounted terminals.

For pipe mounting, it is recommended that this box is used with a nVent RAYCHEM support bracket.

PRODUCT SPECIFICATIONS

Dimensions (in mm)



EM-DS-EU1399-JB82-EN-2211 nVent.com/RAYCHEM | 1

Enclosure

Protection	IP66
Entries	4 x M20 and 4 x M25
Exposure temperature	-35°C to +115°C
Base	Grey glass filled polycarbonate
Lid	Grey polycarbonate
Lid gasket	Foamed polyurethane

Phase terminals

Conta-Clip RK6-10	Din rail mounted
Voltage rating	750 Vac
Max. conductor size	0.5-10 mm ² (solid and stranded)
Current rating	61 A
Quantity	Two cross-connected groups of two

Earth terminals

2 Conta-Clip SL10/35

Mounting

Through holes moulded in the base of the junction box	
Centres	115 x 115 mm
Size	5 mm diameter
Cable gland	Polyamide with locknut for cable diameters from 9 to 16 mm

APPROVALS

For use in ordinary areas; in- and outdoors

Product certification



ORDERING INFORMATION

Part description	JB-82	
PN (Weight)	535679-000 (0.47 kg)	
Accessories		
Junction box support bracket	SB-100, SB-101, SB-110, SB-111	

North America

Tel +1.800.545.6258 Fax +1.800.527.5703 thermal.info@nVent.com

Europe, Middle East, Africa

Tel +32.16.213.502 Fax +32.16.213.604 thermal.info@nVent.com

Asia Pacific

Tel +86.21.2412.1688 Fax +86.21.5426.3167 cn.thermal.info@nVent.com

Latin America

SCHROFF

Tel +1.713.868.4800 Fax +1.713.868.2333 thermal.info@nVent.com

TRACER



Our powerful portfolio of brands:

CADDY ERICO HOFFMAN RAYCHEM