

EASY SPOOL-INSTALLATIEPAKKET MET 10XL2-ZH (ROL VAN 30 M)

CATALOG NUMBER

1244-021262



nVent RAYCHEM contractor packs comprise a fixed length of heating cable supplied in an easy-to-use and carry spool box. The spool allows the installer to feed out the required length easily, reducing installation time and effort.

FEATURES

Unparalleled safety, low smoke zero halogen construction: up to 90% less smoke emissions and improved self-extinguishing properties

Zero halogen: IEC60754-1 tested and compliant

Improved self-extinguishing properties under the IEC62395 flammability test

Energy efficient: self-regulating cable, major savings when used with proportional ambient sensing controller (PASC), no cable overheating possible

Self-regulating technology: cut-to-length on site to mitigate any design variations

Quick and easy installation with the RayClick fast connection system

PRODUCT ATTRIBUTES

Article Number: XL-Trace-InstallerPack-10XL-30m

Heating Cable Technology: Self-Regulating

Supply Voltage: 220 – 240 V

Nominal Voltage: 220 V; 230 V; 240 V

Length: 30 m

Nominal Power Output @ 5°C, 230V: 10 W/m

Max Continuous Exposure Temperature, Power On: 65 °C

Max Intermittent Exposure Temperature, Power On: 85 °C

Max Cumulative Hours for Intermittent Exposure: 800 h

Outer Jacket Material: Low Smoke Zero Halogen

Color: Plum

Ground Path Type: Braid

Min Installation Temperature: -40 °C

Conductor Material: Nickel-Plated Copper

Conductor Quantity: 2

Nominal Cable Weight: 135 g/m

Nominal Height: 6.8 mm

Nominal Width: 13.8 mm

WARNING

nVent products shall be installed and used only as indicated in nVent's product instruction sheets and training materials. Instruction sheets are available at www.nvent.com and from your nVent customer service representative. Improper installation, misuse, misapplication or other failure to completely follow nVent's instructions and warnings may cause product malfunction, property damage, serious bodily injury and death and/or void your warranty.

Noord-Amerika

Tel +1.800.545.6258

Fax +1.800.527.5703

thermal.info@nvent.com

Europe, Middle East, Africa

Tel +32.16.213.511

Fax +32.16.213.604

thermal.info@nvent.com

Asia Pacific

Tel +86.21.2412.1688

Fax +86.21.5426.3167

cn.thermal.info@nvent.com

Latijns-Amerika

Tel +1.713.868.4800

Fax +1.713.868.2333

thermal.info@nvent.com



Our powerful portfolio of brands:
nVent.com CADDY ERICO HOFFMAN RAYCHEM SCHROFF
TRACER