

PRODUCT DATASHEET SMART+ Wifi Ceiling Fan LED Round 550mm + RC

SMART WIFI CEILING FAN | Smart Wifi Ceiling fans for various appliaction areas, combining light and air ventilation



Areas of application

- Kitchens, living rooms, children's rooms or home offices
- For indoor use only

Product benefits

- Clean design, allows for an easy combination with various room styles
- Easy mounting

Product features

- Network protocol: WiFi
- Luminaire with integrated air ventilation
- Adjustable air speed
- Smart control for adjustable color temperature and RGB color control
- Controllable via LEDVANCE SMART+ WiFi App (with minimum Android™ 4.4 or iOS 10.0)
- Remote control included for network independant operation



TECHNICAL DATA

Electrical data

| Nominal wattage | 75.00 W |
|------------------------|---------------|
| Nominal voltage | 3,6 V |
| Nominal current | 10.000 mA |
| Mains frequency | 5060 Hz |
| Power factor λ | > 0.90 |
| Operating mode | Mains voltage |

Photometrical data

| Light color (designation) | Tunable White |
|--|---------------|
| Standard deviation of color matching | < 6 sdcm |
| Nominal luminous flux | 3000 lm |
| Luminous flux | 3000 lm |
| Total luminous flux of contained light sources | 4100 lm |
| Luminous efficacy | 131 lm/W |
| Color temperature | 30006500 K |
| Color rendering index Ra | > 80 |
| Flickering metric (Pst LM) | ≤1 |

Light technical data

| Beam angle | 100 ° |
|---------------|---------|
| Starting time | < 0.5 s |

Dimensions & Weight

| Product weight | 3000.00 g |
|----------------|-----------|
| Length | 602.00 mm |
| Width | 600.00 mm |
| Height | 216.00 mm |

Lifespan



| Number of switching cycles | 15000 |
|----------------------------|---------|
| Lifespan | 30000 h |

Colors & materials

| Product color White | | |
|---------------------|---------------------------------------|--|
| Housing color | White | |
| Body material | Acrylonitrile butadiene styrene (ABS) | |
| Cover material | Polycarbonate (PC) | |

Temperatures & operating conditions

Additional product data

| Mounting location | Ceiling |
|-------------------|---------|
|-------------------|---------|

Capabilities

| Dimmable | Yes |
|------------------------|-----------------|
| Type of connection | Terminal |
| LED module replaceable | Not replaceable |

Certificates & Standards

| Standards | CE / ERP / UKCA |
|--------------------|-----------------|
| Protection class | II |
| Type of protection | IP20 |

EQUIPMENT / ACCESSORIES

- Complete mounting and connecting accessories included
- Control via app or voice control requires compatible Smart home system
- For control via LEDVANCE SMART + WiFi App, a smart phone or Tablet PC is required
- Remote control included

DOWNLOAD DATA

| | Documents and certificates |
|-----|-------------------------------|
| PDF | User instruction |
| POF | Declarations Of Conformity CE |



Documents and certificates



Declarations Of Conformity UKCA

LOGISTICAL DATA

| Product code | Packaging unit (Pieces/Unit) | Dimensions (length x width x height) | Gross weight | Volume |
|---------------|------------------------------|--------------------------------------|--------------|------------|
| 4058075572553 | Folding box 1 | 216 mm x 600 mm x 602 mm | 3688.00 g | 78.02 dm³ |
| 4058075572560 | Shipping box 2 | 620 mm x 452 mm x 620 mm | 9235.00 g | 173.75 dm³ |

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.