

PRODUCT DATASHEET

QTP5 3X14,4X14

QUICKTRONIC® PROFESSIONAL 5 | ECG for FL 16 mm



Areas of application

- Emergency lighting systems acc. to EN 50172 / DIN VDE 0108-100
- Industry
- Open-plan offices, corridors and storage rooms
- Public buildings
- Sports halls and factories
- Strip lighting
- Suitable for emergency lighting (DC operation)
- Modernization of existing systems
- Suitable for luminaires of protection classes I and II

Product benefits

- Long lamp life
- No adverse effect from frequent on/off switching
- Perfect lamp start for applications with motion sensors
- Automatic restart after lamp replacement
- VDE/VDE EMC certified system
- Very high energy efficiency due to cut-off technology

Product features

- Supply voltage: 220...240 V
- Line voltage: 198...264 V
- Line frequency: 0 Hz | 50 Hz | 60 Hz
- Lamp start with optimum filament preheating

- Lifetime: up to 100,000 h (temperature at $T_c = 65\text{ °C}$, max. 10 % failure rate)
- Energy Efficiency Index EEL: A2 BAT
- Automatic shutdown of defective lamps and at end of life (EoL T.2)
- Safety: to EN 61347-2-3
- Lamp operation: to EN 60929

TECHNICAL DATA

Electrical data

Nominal wattage	62.00 W
Nominal voltage	220...240 V
Input voltage DC	176...276 V
U-OUT (working voltage)	430 V
Inrush current	40 A
Mains frequency	50/60 Hz
Max. ECG no. on circuit breaker 10 A (B)	12 ¹⁾
Max. ECG no. on circuit breaker 16 A (B)	19 ¹⁾
Operating frequency	40...50 kHz

¹⁾ Type B

Light technical data

Starting time	1 s
---------------	-----

Dimensions & Weight

Length	280.00 mm
Mounting hole spacing, length	270,0 mm
Width	40.00 mm
Height	21.00 mm
Product weight	211.00 g

Colors & materials

Casing material	Metal
Body material	Metal

Temperatures & operating conditions

Ambient temperature range	-20...+50 °C
Maximum temperature at tc test point	75 °C
Max.housing temperature in case of fault	110 °C
Permitted rel. humidity during operation	5...85 % ¹⁾

¹⁾ Maximum 56 days/year at 85 %

Lifespan

ECG lifetime	100000 h ¹⁾
--------------	------------------------

¹⁾ At T_{case} = 65°C at T_C point / 10% failure rate

Capabilities

Dimmable	No
Max. cable length to lamp/LED module	1.0 m / 1.5 m
Suitable for fixtures with prot. class	I / II
End of lamp life safety shutdown	EOL T.2

Certificates & Standards

Approval marks – approval	VDE / VDE-EMC / ENEC 10 / CE
Standards	Acc. to EN 61347-2-3 / Acc. to EN 55015:2006 + A1:2007 / Acc. to EN 61000-3-2 / Acc. to EN 61547
Protection class	I/II
Type of protection	IP20
Energy efficiency class	A2 BAT
EEL – Energy Label	A2 BAT

LOGISTICAL DATA

Temperature range at storage	-40...+85 °C
------------------------------	--------------

DOWNLOAD DATA

Documents and certificates	
	User instruction
	Declarations Of Conformity CE
	Certificates
CAD/BIM files	
	CAD data 3D PDF

LOGISTICAL DATA

Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
4008321484598	Unpacked 1		211.00 g	
4008321484604	Shipping box 20	304 mm x 115 mm x 171 mm	4475.00 g	5.98 dm ³

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.