

# PRODUCT DATASHEET

## DL ALU DALI DN 200 25 W 3000 K IP44/IP20 WT

DOWNLIGHT ALU DALI | Downlight luminaires with aluminum housing and DALI driver



---

### Areas of application

- Direct replacement for luminaires with compact fluorescent lamps
- General illumination
- Public areas
- Stairways
- Corridors
- Foyers
- Shops

---

### Product benefits

- Advanced functionality due to already included DALI driver
- DALI driver with individual luminaire current set-up already installed
- High luminous efficacy
- Energy savings up to 60 % (compared to luminaires that use CFL lamps)
- Very homogenous light
- Functional design
- Easy installation with fast connection
- 5 years guarantee

---

### Product features



- Advanced applications with DALI light installations
- Diameter of required ceiling cut-out: 150 mm or 200 mm (depending on version)
- Type of protection: IP44


---

**TECHNICAL DATA****Electrical data**


|                                          |                     |
|------------------------------------------|---------------------|
| Nominal wattage                          | 25.00 W             |
| Nominal voltage                          | 220...240 V         |
| Mains frequency                          | 0/50/60 Hz          |
| Nominal current                          | 110.000 mA          |
| Inrush current                           | 23 A                |
| Inrush current time $T_{h50}$            | 151 $\mu$ s         |
| Max. no. of lum. on circuit break. B16 A | 32                  |
| Max. no. of lum. on circuit break. C10 A | 31                  |
| Max. no. of lum. on circuit break. C16 A | 53                  |
| Power factor $\lambda$                   | > 0.90              |
| Total harmonic distortion                | < 20 %              |
| Protection class                         | II                  |
| Operating mode                           | External LED driver |

**Photometrical data**

|                                              |                           |
|----------------------------------------------|---------------------------|
| Luminous flux                                | 2250 lm                   |
| Luminous efficacy                            | 90 lm/W                   |
| Color temperature                            | 3000 K                    |
| Light color (designation)                    | Warm White                |
| Color rendering index Ra                     | > 80                      |
| Standard deviation of color matching         | $\leq 6$ sdc <sub>m</sub> |
| Luminous intensity                           | -                         |
| Flickering metric (Pst LM)                   | -                         |
| Stroboscope effect metric (SVM)              | -                         |
| Photobiological safety group acc. to EN62778 | RG0                       |
| Photobiological safety group acc. to EN62471 | RG0                       |
| Beam angle                                   | 100 °                     |




LDC typ cone



LDC typ polar

Dimensions & Weight

|                |           |
|----------------|-----------|
| Diameter       | 215.00 mm |
| Height         | 61.00 mm  |
| Product weight | 600.00 g  |



Materials & Colors

|               |       |
|---------------|-------|
| Product color | White |
|---------------|-------|

|                                            |                               |
|--------------------------------------------|-------------------------------|
| Housing color                              | White                         |
| Body material                              | Aluminum                      |
| Cover material                             | Polymethylmethacrylate (PMMA) |
| Glow Wire Test according to IEC 60695-2-12 | 650 °C                        |
| Mercury content                            | 0.0 mg                        |

Application & Mounting

|                                        |                            |
|----------------------------------------|----------------------------|
| Ambient temperature range              | -20...+45 °C               |
| Type of connection                     | Screwless terminal, 5-Pole |
| Type of protection                     | IP44/IP20                  |
| Protection class IK (shock resistance) | IK02                       |
| Dimmable                               | Yes                        |
| Type of dimming                        | DALI                       |
| Mounting type                          | Recessed                   |
| Mounting location                      | Ceiling                    |
| Application environment                | Indoor                     |
| Mounting diameter                      | 200 mm                     |
| Mounting depth                         | 120 mm                     |
| LED module replaceable                 | Not replaceable            |
| With light source                      | Yes                        |

Lifespan

|                            |         |
|----------------------------|---------|
| Lifespan L70/B50 at 25 °C  | 50000 h |
| Lifespan L80/B10 at 25 °C  | 45000 h |
| Lifespan L90/B10 at 25 °C  | 30000 h |
| Number of switching cycles | 100000  |

Certificates & Standards

|                                                      |               |
|------------------------------------------------------|---------------|
| Standards                                            | CE / CB / EAC |
| Luminaire with limited surface temperature, "D sign" | No            |
| Ball shot safe                                       | No            |

Additional product data

|                       |              |
|-----------------------|--------------|
| Number of illuminants | Not relevant |
|-----------------------|--------------|

DOWNLOAD DATA

## Documents and certificates



User instruction



Addon Technical Information



Declarations Of Conformity CE



Declarations Of Conformity UKCA

## Photometric and lighting design files



IES file (IES)



LDT file (Eulumdat)



ULD file (DIALux)



ROLF file (RELUX)



UGR file (UGR table)



LDC typ cone



LDC typ polar

## CAD/BIM files



BIM\_Revit\_3D



CAD\_STEP\_3D

## Tender texts



Tender documents


## LOGISTICAL DATA

| Product code  | Packaging unit (Pieces/Unit) | Dimensions (length x width x height) | Gross weight | Volume                |
|---------------|------------------------------|--------------------------------------|--------------|-----------------------|
| 4058075091610 | Folding box<br>1             | 225 mm x 225 mm x 110 mm             | 775.00 g     | 5.57 dm <sup>3</sup>  |
| 4058075091627 | Shipping box<br>8            | 658 mm x 466 mm x 263 mm             | 7660.00 g    | 80.64 dm <sup>3</sup> |

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

---

### ADDITIONAL CATALOG INFORMATION



### References / Links

– For Guarantee see [www.ledvance.com/guarantee](http://www.ledvance.com/guarantee)

---

### DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.