

PRODUCT DATASHEET

TruSys® PFM ENERGY RAIL 5P 1500 END

TruSys® PERFORMANCE ENERGY RAIL 5 POLE | 5-pole mounting rail

Areas of application

- Industry halls, high rack warehouse, garages, hardware stores

Product benefits

- Simple installation
- High flexibility thanks to two available lengths (1500 mm, 3000 mm and 1500 mm end rail)

Product features

- Through wired with 5 core cable
- Different lengths available
- Electrical connection internal at the first luminaire, no external connection unit required
- Steel-sheet housing
- End-Rail without electrical and mechanical connectors



TECHNICAL DATA

Dimensions & Weight

Length	1500 mm
Width	70.2 mm
Height	38.8 mm
Product weight	1630.00 g

Materials & Colors

Product color	White
---------------	-------

Application & Mounting

Ambient temperature range	-25...+60 °C
Type of protection	IP20
Mounting type	Surface
Mounting location	Ceiling
With light source	No

Certificates & Standards

Standards	CE
-----------	----

EQUIPMENT / ACCESSORIES

– Various accessories available

DOWNLOAD DATA

CAD/BIM files
CAD_STEP_3D

LOGISTICAL DATA

Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
4058075354753	Shipping box 1	1,521 mm x 83 mm x 57 mm	1905.00 g	7.20 dm³

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

choose one Professional

Country Deutsch

[myLEDVANCE](#)

The server returned a "500 Internal Server Error".

Something is broken. Please let us know what you were doing when this error occurred. We will fix it as soon as possible. Sorry for any inconvenience caused.

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.

choose one

Country

[myLEDVANCE](#)