

# PRODUCT DATASHEET

## Submarine Integrated 1.2M 36W 4000K

SUBMARINE® Integrated | Damp-proof luminaires with integrated LED module



---

### Areas of application

- Basements, garages, warehouses

---

### Product benefits

- Easy and quick installation
- Very homogenous light
- Extremely bright

---

### Product features

- Dust-protected and jet-proof (IP65)
- Not dimmable



TECHNICAL DATA

Electrical data


|                           |                       |
|---------------------------|-----------------------|
| Nominal wattage           | 36.00 W               |
| Nominal voltage           | 220...240 V           |
| Mains frequency           | 50...60 Hz            |
| Nominal current           | 157.000 mA            |
| Power factor $\lambda$    | > 0.90                |
| Total harmonic distortion | < 20 %                |
| Protection class          | II                    |
| Operating mode            | Integrated LED driver |

Photometrical data

|                                                |            |
|------------------------------------------------|------------|
| Luminous flux                                  | 3000 lm    |
| Total luminous flux of contained light sources | 3600 lm    |
| Luminous efficacy                              | 83 lm/W    |
| Color temperature                              | 4000 K     |
| Light color (designation)                      | Cool White |
| Color rendering index Ra                       | $\geq 80$  |
| Standard deviation of color matching           | < 5 sdcm   |
| Flickering metric (Pst LM)                     | <10        |
| Photobiological safety group acc. to EN62778   | RG0        |
| Beam angle                                     | 120 °      |

Dimensions & Weight

|                |            |
|----------------|------------|
| Length         | 1180.00 mm |
| Width          | 86.00 mm   |
| Height         | 66.00 mm   |
| Product weight | 1210.00 g  |



Materials & Colors

|                 |                    |
|-----------------|--------------------|
| Product color   | Gray               |
| Housing color   | Gray               |
| Body material   | Polycarbonate (PC) |
| Mercury content | 0.0 mg             |

### Application & Mounting

|                                        |                         |
|----------------------------------------|-------------------------|
| Ambient temperature range              | -20...+40 °C            |
| Type of connection                     | Terminal, 2-Pole (L, N) |
| Type of protection                     | IP65                    |
| Protection class IK (shock resistance) | IK06                    |
| Dimmable                               | No                      |
| Mounting type                          | Surface                 |
| Mounting location                      | Ceiling / Wall          |
| Application environment                | Indoor                  |
| LED module replaceable                 | Not replaceable         |
| With light source                      | Yes                     |

### Lifespan

|                            |       |
|----------------------------|-------|
| Number of switching cycles | 25000 |
|----------------------------|-------|

### Certificates & Standards

|                                                      |                 |
|------------------------------------------------------|-----------------|
| Standards                                            | CE / EAC / UKCA |
| Luminaire with limited surface temperature, "D sign" | No              |

### EQUIPMENT / ACCESSORIES

- Complete mounting and connecting accessories included

### DOWNLOAD DATA

| Documents and certificates                                                         |                               |
|------------------------------------------------------------------------------------|-------------------------------|
|  | User instruction              |
|  | Packaging insert              |
|  | Declarations Of Conformity CE |

## Documents and certificates



Declarations Of Conformity UKCA

## LOGISTICAL DATA

| Product code  | Packaging unit (Pieces/Unit) | Dimensions (length x width x height) | Gross weight | Volume                |
|---------------|------------------------------|--------------------------------------|--------------|-----------------------|
| 4058075260412 | Folding box<br>1             | 89 mm x 1,210 mm x 69 mm             | 1376.00 g    | 7.43 dm <sup>3</sup>  |
| 4058075260429 | Shipping box<br>8            | 1,230 mm x 200 mm x 304 mm           | 11848.00 g   | 74.78 dm <sup>3</sup> |

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

## DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.