

PRODUCT DATASHEET LUNETTA Hall Sensor White

LUNETTA® Hall Sensor | Socket night light with motion sensor



Areas of application

- Bedrooms
- Children's bedrooms
- Entrances / Hallways
- For indoor use only

Product benefits

- Demand based lighting and energy saving thanks to motion and daylight sensor
- Plug and Play due to EU Plug
- Energy-efficient thanks to LED technology

Product features

- Integrated light and motion sensor



TECHNICAL DATA

Electrical data


Nominal wattage	0.70 W
Nominal voltage	220240 V
Mains frequency	5060 Hz
Nominal current	30.000 mA
Max. no. of lum. on circuit break. B16 A	-
Max. no. of lum. on circuit break. C10 A	-
Max. no. of lum. on circuit break. C16 A	-
Protection class	П
Operating mode	Mains voltage

Photometrical data

Luminous flux	10 lm
Color temperature	3000 K
Light color (designation)	Warm White
Color rendering index Ra	≥80

Dimensions & Weight

Length	67.00 mm
Width	84.00 mm
Height	73.00 mm
Product weight	60.00 g



Materials & Colors

Product color	White
Housing color	White
Body material	Polycarbonate (PC) Acrylonitrile butadiene styrene (ABS)
Light emitting surface material	Plastic

Mercury content	0.0 mg	
pplication & Mounting		
Ambient temperature range	-20+40 °C	
Type of connection	Plug type C (EU)	
Type of protection	IP20	
Dimmable	No	
Mounting type	Surface	
Mounting location	Socket	
Application environment	Indoor	
LED module replaceable	Not replaceable	
With light source	Yes	
ifespan		
Lifespan L70/B50 at 25 °C	25000 h	
Lifespan L70/B50 at 25 °C	25000 h	
Lifespan L70/B50 at 25 °C	25000 h Motion	
Lifespan L70/B50 at 25 °C ensor Type of sensor		
Lifespan L70/B50 at 25 °C ensor Type of sensor Sensor technology	Motion	
Lifespan L70/B50 at 25 °C ensor Type of sensor Sensor technology Sensor detection angle	Motion Passive infrared (PIR)	
Lifespan L70/B50 at 25 °C ensor Type of sensor Sensor technology Sensor detection angle Sensor controlled switching time	Motion Passive infrared (PIR) 120 °	
·	Motion Passive infrared (PIR) 120 ° 10 s10 min	
Lifespan L70/B50 at 25 °C Sensor Type of sensor Sensor technology Sensor detection angle Sensor controlled switching time Detection range of motion sensor	Motion Passive infrared (PIR) 120 ° 10 s10 min 9 m	

DOWNLOAD DATA

	Documents and certificates
PDF	Packaging insert
PDF	Declarations Of Conformity CE

LOGISTICAL DATA

Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
4058075266780	Blister 1	68 mm x 140 mm x 195 mm	80.00 g	1.86 dm³
4058075266797	Shipping box 6	421 mm x 154 mm x 210 mm	671.00 g	13.62 dm³

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.