

# PRODUCT DATASHEET

## ENDURA Garden 3 Dots Extension 3000K

ENDURA GARDEN DOT | Decorative light dots for outdoor use



---

### Areas of application

- Gardens, balconies and other outdoor areas

---

### Product benefits

- Easy and quick installation

---

### Product features

- Protection class (dots): IP65
- Protection class (power supply): IP44
- Extension up to maximum 18 dots
- Color temperature: 3,000 K (Warm White)

## Oops! An Error Occurred

The server returned a "500 Internal Server Error".

Something is broken. Please let us know what you were doing when this error occurred. We will fix it as soon as possible. Sorry for any inconvenience caused.

The server returned a "500 Internal Server Error".

Something is broken. Please let us know what you were doing when this error occurred. We will fix it as soon as possible. Sorry for any inconvenience caused.

TECHNICAL DATA

Electrical data


|                  |               |
|------------------|---------------|
| Nominal wattage  | 2.10 W        |
| Nominal voltage  | 220...240 V   |
| Mains frequency  | 50...60 Hz    |
| Power factor λ   | > 0.5         |
| Protection class | III           |
| Operating mode   | Mains voltage |

Photometrical data

|                                                |            |
|------------------------------------------------|------------|
| Luminous flux                                  | 160 lm     |
| Total luminous flux of contained light sources | 210 lm     |
| Luminous efficacy                              | 52 lm/W    |
| Color temperature                              | 3000 K     |
| Light color (designation)                      | Warm White |
| Color rendering index Ra                       | ≥80        |
| Standard deviation of color matching           | ≤6 sdc     |
| Beam angle                                     | 33.00 °    |

Dimensions & Weight

|                |          |
|----------------|----------|
| Diameter       | 23.00 mm |
| Width          | 23.00 mm |
| Height         | 96.00 mm |
| Product weight | 80.00 g  |



Materials & Colors

|                |                    |
|----------------|--------------------|
| Product color  | Clear              |
| Body material  | Polycarbonate (PC) |
| Cover material | Polycarbonate (PC) |

choose one Professional

Country Deutsch  
myLEDVANCE

## Application & Mounting

|                           |                  |
|---------------------------|------------------|
| Ambient temperature range | -20...+40 °C     |
| Type of connection        | Plug type C (EU) |
| Type of protection        | IP65             |
| Dimmable                  | No               |
| Mounting type             | Ground spike     |
| Mounting location         | Ground           |
| Application environment   | Outdoor          |
| LED module replaceable    | Not replaceable  |
| With light source         | Yes              |

## Lifespan

|                            |         |
|----------------------------|---------|
| Lifespan L70/B50 at 25 °C  | 25000 h |
| Number of switching cycles | 12500   |

## Certificates & Standards

|           |          |
|-----------|----------|
| Standards | CE / EAC |
|-----------|----------|

## EQUIPMENT / ACCESSORIES

- Power supply included only in basic set
- Complete mounting and connecting accessories included

## DOWNLOAD DATA

| Documents and certificates                                                         |                               |
|------------------------------------------------------------------------------------|-------------------------------|
|  | User instruction              |
|  | Declarations Of Conformity CE |

## LOGISTICAL DATA

| Product code  | Packaging unit (Pieces/Unit) | Dimensions (length x width x height) | Gross weight | Volume               |
|---------------|------------------------------|--------------------------------------|--------------|----------------------|
| 4058075478510 | Folding box<br>1             | 102 mm x 44 mm x 109 mm              | 100.00 g     | 0.49 dm <sup>3</sup> |

choose one Professional

Country Deutsch

[myLEDVANCE](#)

**The server returned a "500 Internal Server Error".**

Something is broken. Please let us know what you were doing when this error occurred. We will fix it as soon as possible. Sorry for any inconvenience caused.

|               |                   |                          |          |                      |
|---------------|-------------------|--------------------------|----------|----------------------|
| 4058075478527 | Shipping box<br>4 | 180 mm x 125 mm x 120 mm | 534.00 g | 2.70 dm <sup>3</sup> |
|---------------|-------------------|--------------------------|----------|----------------------|

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

**DISCLAIMER**

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.

**Oops! An Error Occurred**

**The server returned a "500 Internal Server Error".**

Something is broken. Please let us know what you were doing when this error occurred. We will fix it as soon as possible. Sorry for any inconvenience caused.