

The server returned a "500 Internal Server Error".

Something is broken. Please let us know what you were doing when this error occurred. We will fix it as soon as possible. Sorry for any inconvenience caused.

FICHA TÉCNICA DEL PRODUCTO

DALI magic

DALI magic | Interfaz de programación de USB a DALI



Áreas de aplicación

- Configuration of DALI ECG functions
- Monitoring of DALI installations

Beneficios del producto

DALI wizard software features (included)

- Intuitive configuration of up to 64 DALI electronic control gears
- Offline / Online configuration of DALI installations
- "DALI-Spy"-functionality for recording DALI line data flow

Tuner4TRONIC software features

- Programming of OSRAM ECG
- Suitable for the shop floor environments
- Performs fast manual and automatic programming
- Easily enables the use of the pre-parameterization service

Características del producto

- USB DALI converter for Tuner4TRONIC and DALI wizard software for Windows PC
- Pushbutton to test DALI dimming without need of connection to computer
- Powered by USB or by included universal power supply
- Integrated automatic DALI supply of up to 64 devices (up to 4 if powered by USB)

Oops! An Error Occurred

The server returned a "500 Internal Server Error".

The server returned a "500 Internal Server Error".

Something is broken. Please let us know what you were doing when this error occurred. We will fix it as soon as possible. Sorry for any inconvenience caused.

INFORMACION TÉCNICA

DATOS ELÉCTRICOS

Potencia nominal	7,00 W
Tensión nominal	220...240 V
Frecuencia de red	50/60 Hz

DIMENSIONES Y PESO

Largo	120,0 mm
Ancho	120.00 mm
Ancho (incl. Luminarias redondas)	120.00 mm
Alto	28.00 mm
Altura (luminarias incluidas)	28.00 mm
Peso del producto	370,00 g

COLORES Y MATERIALES

Color del producto	blanco
--------------------	--------

TEMPERATURAS Y CONDICIONES DE FUNCIONAMIENTO

Margen de temperatura ambiente	+15...+50 °C
--------------------------------	--------------

PRESTACIONES

Regulable	Sí
Interfaz DIM	DALI

CERTIFICADOS Y ESTÁNDARES

Clase de protección	I
Tipo de protección	IP20

Equipamiento / Accesorios

- Universal power supply (100...240 V_{AC}, 5.9 V_{DC}, 1.15 A, EU plug)
- USB cable (male A to male B), 180 cm
- Bipolar plug for DALI connection

DESCARGAS

Documentos y certificados	
	User instruction
	Declarations Of Conformity CE

Oops! An Error Occurred

The server returned a "500 Internal Server Error".

The server returned a "500 Internal Server Error".

Something is broken. Please let us know what you were doing when this error occurred. We will fix it as soon as possible. Sorry for any inconvenience caused.

DATOS LOGISTICOS

Código de producto	Cantidad por caja (unidad/master)	Dimensiones (longitud x largo x altura)	Peso bruto	Volumen
4052899039551	Embalaje de envío 1	148 mm x 98 mm x 135 mm	376.00 g	1.96 dm ³

El codigo de producto mencionado describe la cantidad minima de unidades que puede ser comprada. Una unidad de transporte puede contener uno o más productos individuales. Cuando se realiza la compra, para las cantidades porfavor ingrese una o varias unidades de envio.

Referencias / Enlaces

– Software compatible disponible en www.ledvance.com/software

DESCARGO DE RESPONSABILIDAD

Sujeto a cambio sin aviso. Errores y omisiones exceptuadas. Asegurese de utilizar la version más reciente.

Oops! An Error Occurred

The server returned a "500 Internal Server Error".