

The server returned a "500 Internal Server Error".

Something is broken. Please let us know what you were doing when this error occurred. We will fix it as soon as possible. Sorry for any inconvenience caused.

FICHA TÉCNICA DEL PRODUCTO

QTi 1X28/54/35/49 GII

QUICKTRONIC® INTELLIGENT | ECE para FL 16 mm



Áreas de aplicación

- Emergency lighting systems acc. to EN 50172 / DIN VDE 0108-100
- Industry
- Open-plan offices, corridors and storage rooms
- Public buildings
- Sports halls and factories
- Strip lighting
- Suitable for emergency lighting (DC operation)
- Modernization of existing systems
- Suitable for luminaires of protection classes I and II

Beneficios del producto

- Long lamp life
- No adverse effect from frequent on/off switching
- Automatic restart after lamp replacement
- Perfect lamp start for applications with motion sensors
- VDE/VDE EMC certified system
- Very high energy efficiency due to cut-off technology

Características del producto

- Supply voltage: 220...240 V
- Line voltage: 198...264 V
- Line frequency: 0 Hz | 50 Hz | 60 Hz
- Lamp start with optimum filament preheating

Oops! An Error Occurred

The server returned a "500 Internal Server Error".

Something is broken. Please let us know what you were doing when this error occurred. We will fix it as soon as possible. Sorry for any inconvenience caused.

- Lifetime: > 100,000 h (for T = 65 °C at T₀)
- Energy Efficiency Index EEI: A2 BAT
- Automatic shutdown of defective lamps and at end of life (EoL T.2)
- Safety: to EN 61347-2-3
- Lamp operation: to EN 60929

Oops! An Error Occurred

The server returned a "500 Internal Server Error".

Something is broken. Please let us know what you were doing when this error occurred. We will fix it as soon as possible. Sorry for any inconvenience caused.

The server returned a "500 Internal Server Error".

Something is broken. Please let us know what you were doing when this error occurred. We will fix it as soon as possible. Sorry for any inconvenience caused.

INFORMACION TECNICA

DATOS ELÉCTRICOS

Potencia nominal	59,00 W
Tensión nominal	220...240 V
Tensión de entrada	198...264 V
Tensión cc	176...276 V
U-OUT	330 V
Corriente de encendido IP	24 A
Frecuencia de red	50/60 Hz
Nº de ECE máximos con automático 10 A (B)	17 ¹⁾
Nº de ECE máximos con automático 16 A (B)	28 ¹⁾
Frecuencia de funcionamiento	42...85 kHz

1) Tipo B

Datos técnicos de iluminación

Tiempo de arranque	1 s
--------------------	-----

DIMENSIONES Y PESO

Largo	360.00 mm
Distancia entre taladros longitud	350,0 mm
Ancho	30.00 mm
Ancho (incl. Luminarias redondas)	30.00 mm
Alto	21.00 mm
Altura (luminarias incluidas)	21.00 mm
Peso del producto	235,00 g

COLORES Y MATERIALES

Material de la carcasa	Metal
Material del cuerpo	Metal

TEMPERATURAS Y CONDICIONES DE FUNCIONAMIENTO

Margen de temperatura ambiente	-20...+50 °C
Temp. máx. en el punto de prueba tc	75 °C
Temp. máx de la carcasa en caso de fallo	110 °C
Humedad rel. permitida durante el func.	5...85 % ¹⁾

Oops! An Error Occurred

The server returned a "500 Internal Server Error".

Something is broken. Please let us know what you were doing when this error occurred. We will fix it as soon as possible. Sorry for any inconvenience caused.

The server returned a "500 Internal Server Error".

Something is broken. Please let us know what you were doing when this error occurred. We will fix it as soon as possible. Sorry for any inconvenience caused.

Vida media

ECE vida útil	100000 h ¹⁾
---------------	------------------------

1) En tcase = 65°C a tc punto / 10 % indice de fallos

PRESTACIONES

Regulable	No
Longitud cableado máx. ECE/lámpara REM	2.0 m / 1.0 m
Apto para luminarias con clase de prot.	I / II
Apto para iluminación de emergencia	Sí
Fin vida útil de la lámp., desco. seg.	EOL T.2

CERTIFICADOS Y ESTÁNDARES

Símbolos de homologación	VDE / VDE-EMC / ENEC 10 / CE
Normas	Según EN 61347-2-3 / Según EN 60929 / Según EN 55015:2006 + A1:2007 / Según EN 61000-3-2 / Según EN 61547
Clase de protección	II
Tipo de protección	IP20
Clase de eficiencia energética	A2
EEL – Etiqueta energética	A2 BAT

DATOS LOGÍSTICOS

Temperatura de almacenamiento	-40...+85 °C
-------------------------------	--------------

INFORMACIÓN ADICIONAL DEL PRODUCTO

- In order to achieve good radio interference suppression:
1. Keep the cable between ECG and lamp as short as possible.
 2. The single lamp wires must be routed as close as possible to each other, whereas the lines of the different lamp ends must be routed separately.

DESCARGAS

Documentos y certificados	
	User instruction
	Declarations Of Conformity CE

Oops! An Error Occurred

The server returned a "500 Internal Server Error".

Something is broken. Please let us know what you were doing when this error occurred. We will fix it as soon as possible. Sorry for any inconvenience caused.

The server returned a "500 Internal Server Error".

Something is broken. Please let us know what you were doing when this error occurred. We will fix it as soon as possible. Sorry for any inconvenience caused.


	Certificates
Archivos CAD/BIM	
	CAD data 3D PDF



DATOS LOGÍSTICOS

Código de producto	Cantidad por caja (unidad/master)	Dimensiones (longitud x largo x altura)	Peso bruto	Volumen
4008321383358	Sin embalaje 1		235.00 g	
4008321383365	Embalaje de envío 20	392 mm x 98 mm x 165 mm	4919.99 g	6.34 dm³

El codigo de producto mencionado describe la cantidad minima de unidades que puede ser comprada. Una unidad de transporte puede contener uno o más productos individuales. Cuando se realiza la compra, para las cantidades porfavor ingrese una o varias unidades de envio.



DESCARGO DE RESPONSABILIDAD

Sujeto a cambio sin aviso. Errores y omisiones exceptuadas. Asegurese de utilizar la version más reciente.

Oops! An Error Occurred

The server returned a "500 Internal Server Error".

Something is broken. Please let us know what you were doing when this error occurred. We will fix it as soon as possible. Sorry for any inconvenience caused.