

The server returned a "500 Internal Server Error".

Something is broken. Please let us know what you were doing when this error occurred. We will fix it as soon as possible. Sorry for any inconvenience caused.

PRODUCTINFORMATIEBLAD

Spotlight Recess Set Incl. Osram LED 3x2.6W GU10 White

LED SPOT SET RECESS GU10 | Inbouwspot inclusief GU10 lamp



Toepassingsgebieden

- Binnentoepassingen
- Gangen, entrees, trappenhuizen, woonkamers, kelders
- Slaapkamers
- Keukens

Productvoordelen

- Lichtbron inbegrepen

Productkenmerken

- GU10 lamp inbegrepen
- Materiaal behuizing: metaal

Oops! An Error Occurred

The server returned a "500 Internal Server Error".

Something is broken. Please let us know what you were doing when this error occurred. We will fix it as soon as possible. Sorry for any inconvenience caused.

The server returned a "500 Internal Server Error".

Something is broken. Please let us know what you were doing when this error occurred. We will fix it as soon as possible. Sorry for any inconvenience caused.

TECHNISCHE GEGEVENS

ELEKTRISCHE GEGEVENS

Nominale vermogen	2,60 W
Nominale spanning	220...240 V
Netfrequentie	50...60 Hz
Nominale stroom	25,000 mA
Inschakelstroom	0,3 A
Inschakelstroomtijd T _{h50}	260 µs
Max. armaturen op stroomonderbreke B16 A	53
Max. armaturen op stroomonderbreke C10 A	53
Max. armaturen op stroomonderbreke C16 A	85
Arbeidsfactor λ	> 0,4
Totale harmonische vervorming	< 20 %
Veiligheidsklasse	II

Fotometrische gegevens

Lichtstroom	230 lm
Totale lichtstroom van ingesloten lichtbronnen	230 lm
Lichtstroom efficiëntie	88 lm/W
Kleurtemperatuur	2700 K
Lichtkleur	Warm White
Kleurweergave-index Ra	≥80
Standaardafwijking van kleurproeven	≤6 sdc _m
Lichtsterkte	400 cd
Flikkerwaarde Pst LM	<1
Stroboscoopeffect waarde SVM	<0,4
Fotobiologische veiligheidsgroep EN62778	RG1
Fotobiologische veiligheidsgroep EN62471	RG1
Stralingshoek	36 °

AFMETINGEN & GEWICHT

Diameter	80,00 mm
Hoogte	95.00 mm
Product gewicht	130,00 g

Oops! An Error Occurred

The server returned a "500 Internal Server Error".

Something is broken. Please let us know what you were doing when this error occurred. We will fix it as soon as possible. Sorry for any inconvenience caused.

The server returned a "500 Internal Server Error".

Something is broken. Please let us know what you were doing when this error occurred. We will fix it as soon as possible. Sorry for any inconvenience caused.

MATERIALEN & KLEUREN

Kleur van het product	Wit
Kleur behuizing	Wit
Body materiaal	Steel
Glow Wire Test volgens IEC 60695-2-12	850 °C
Kwikgehalte	0.0 mg

TOEPASSING & MONTAGE

Omgevingstemperatuur bereik	-20...+40 °C
Opslagtemperatuur	-20...+80 °C
Type aansluiting	Schroefterminal
Type bescherming	IP20
Dimbaar	Nee
Montagetype	Recessed
Montagelocatie	Plafond
Toepassingsomgeving	Indoor
Diameter inbouw opening	60,0 mm
Inbouwdiepte	140 mm
Instelbaar	Nee
Met lichtbron	Ja
Omschrijving van de fitting	GU10

Levensduur

Levensduur L70/B50 @ 25 °C	25000 h
Aantal schakelcycli	100000

CERTIFICATEN & NORMEN

Normen	CE / UKCA
Gelimiteerde oppervlaktetemperatuur	Nee

AANVULLENDE PRODUCTGEGEVENS

Aantal inbegrepen lichtbronnen	3
--------------------------------	---

Oops! An Error Occurred

The server returned a "500 Internal Server Error".

Something is broken. Please let us know what you were doing when this error occurred. We will fix it as soon as possible. Sorry for any inconvenience caused.

The server returned a "500 Internal Server Error".

Something is broken. Please let us know what you were doing when this error occurred. We will fix it as soon as possible. Sorry for any inconvenience caused.

- Complete montage- en verbindingaccessoires inbegrepen

DOWNLOADS

Documenten en certificaten	
	User instruction
	Packaging insert
	Declarations Of Conformity CE
	Declarations Of Conformity UKCA

LOGISTIEKE GEGEVENS

Productcode	Verpakkingseenheid (stuks per verpakking)	Afmetingen (lengte x breedte x hoogte)	Brutogewicht	Volume
4058075611313	Vouwdoos 3	100 mm x 72 mm x 287 mm	455.00 g	2.07 dm ³
4058075611320	Verzenddoos 18	237 mm x 217 mm x 319 mm	3056.00 g	16.41 dm ³

De genoemde productcodes beschrijven de kleinste hoeveelheid die besteld kan worden. Eén verzendeenheid kan bestaan uit één of meer afzonderlijke producten. Bij het plaatsen van een order enkele of veelvouden van de verpakkingseenheid invoeren.

DISCLAIMER

Onder voorbehoud van verandering zonder kennisgeving. Fouten en drukfouten voorbehouden. Zorg ervoor dat u de meest recente versie gebruikt.

Oops! An Error Occurred

The server returned a "500 Internal Server Error".

Something is broken. Please let us know what you were doing when this error occurred. We will fix it as soon as possible. Sorry for any inconvenience caused.