

The server returned a "500 Internal Server Error".

Something is broken. Please let us know what you were doing when this error occurred. We will fix it as soon as possible. Sorry for any inconvenience caused.

# PRODUCT DATASHEET

## SPC.T26 20 P 2.3W 865 FR E14

LED SPECIAL T26 P | Special LED lamps for refrigerators



---

### Areas of application

- Small designer luminaires
- Domestic refrigerators
- Sewing machines
- Outdoor use in suitable outdoor luminaires only

---

### Product benefits

- Extremely small dimensions
- Good all-around light emission
- Ideal for decorative and free-burning applications
- Long lifetime of up to 15,000 h
- Four year guarantee

---

### Product features

- LED alternative to conventional high voltage lamps
- Good quality of light; color rendering index  $R_a$ :  $\geq 80$ ; constant chromaticity

## Oops! An Error Occurred

The server returned a "500 Internal Server Error".

Something is broken. Please let us know what you were doing when this error occurred. We will fix it as soon as possible. Sorry for any inconvenience caused.

The server returned a "500 Internal Server Error".

Something is broken. Please let us know what you were doing when this error occurred. We will fix it as soon as possible. Sorry for any inconvenience caused.


TECHNICAL DATA

Electrical data

|                                          |             |
|------------------------------------------|-------------|
| Nominal wattage                          | 2.3 W       |
| Construction wattage                     | 2.30 W      |
| Nominal voltage                          | 220...240 V |
| Claimed equiv. conventional lamp power   | 20 W        |
| Nominal current                          | 22 mA       |
| Type of current                          | AC          |
| Inrush current                           | 4.6 A       |
| Operating frequency                      | 50/60 Hz    |
| Mains frequency                          | 50/60 Hz    |
| Max. lamp no. on circuit break. 10 A (B) | 106         |
| Max. lamp no. on circuit break. 16 A (B) | 169         |
| Total harmonic distortion                | < 175 %     |
| Power factor λ                           | 0.40        |

Photometrical data

|                                         |               |
|-----------------------------------------|---------------|
| Luminous flux                           | 200 lm        |
| Nominal useful luminous flux 90°        | 200 lm        |
| Luminous efficacy                       | 87 lm/W       |
| Lumen main.fact.at end of nom.life time | 0.70          |
| Light color (designation)               | Cool Daylight |
| Color temperature                       | 6500 K        |
| Color rendering index Ra                | 80            |
| Light color                             | 865           |
| Standard deviation of color matching    | ≤6 sdcn       |
| Rated LLMF at 6,000 h                   | 0.80          |
| Flickering metric (Pst LM)              | ≤1            |
| Stroboscope effect metric (SVM)         | ≤0.4          |



Oops! An Error Occurred

The server returned a "500 Internal Server Error".

Something is broken. Please let us know what you were doing when this error occurred. We will fix it as soon as possible. Sorry for any inconvenience caused.

The server returned a "500 Internal Server Error".

Something is broken. Please let us know what you were doing when this error occurred. We will fix it as soon as possible. Sorry for any inconvenience caused.

Light technical data

|                                    |          |
|------------------------------------|----------|
| Beam angle                         | 200 °    |
| Warm-up time (60 %)                | < 0.50 s |
| Starting time                      | < 0.5 s  |
| Rated beam angle (half peak value) | 200.00 ° |

Dimensions & Weight

|                  |          |
|------------------|----------|
| Overall length   | 58.00 mm |
| Diameter         | 25.00 mm |
| Maximum diameter | 25 mm    |
| Product weight   | 12.00 g  |

Temperatures & operating conditions

|                                      |              |
|--------------------------------------|--------------|
| Ambient temperature range            | -20...+40 °C |
| Maximum temperature at tc test point | 72 °C        |

Lifespan

|                                     |         |
|-------------------------------------|---------|
| Lifespan                            | 15000 h |
| Number of switching cycles          | 100000  |
| Lumen maintenance at end of serv    | 0.70    |
| Rated lamp survival factor at 6,000 | ≥ 0.90  |

Additional product data

|                             |                                                                                                                                                                                                                                                                                                                                              |
|-----------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Base (standard designation) | E14                                                                                                                                                                                                                                                                                                                                          |
| Mercury content             | 0.0 mg                                                                                                                                                                                                                                                                                                                                       |
| Mercury-free                | Yes                                                                                                                                                                                                                                                                                                                                          |
| Design / version            | Frosted                                                                                                                                                                                                                                                                                                                                      |
| Product remark              | All technical parameters apply to the entire lamp / Due to the complex production process for light-emitting diodes, the typical values shown for the technical LED parameters are purely statistical values that do not necessarily match the actual technical parameters of each individual product, which can vary from the typical value |

Capabilities

|          |    |
|----------|----|
| Dimmable | No |
|----------|----|

Certificates & Standards

Oops! An Error Occurred

The server returned a "500 Internal Server Error".

Something is broken. Please let us know what you were doing when this error occurred. We will fix it as soon as possible. Sorry for any inconvenience caused.

The server returned a "500 Internal Server Error".

Something is broken. Please let us know what you were doing when this error occurred. We will fix it as soon as possible. Sorry for any inconvenience caused.

|                                              |                |
|----------------------------------------------|----------------|
| Energy consumption                           | 3.00 kWh/1000h |
| Type of protection                           | IP20           |
| Standards                                    | CE / EAC       |
| Photobiological safety group acc. to EN62778 | RG1            |

1) Energy efficiency class (EEC) on a scale of A (highest efficiency) to G (lowest efficiency)

Country-specific categorizations

|                 |                 |
|-----------------|-----------------|
| Order reference | LED T26 20 2.3W |
|-----------------|-----------------|

LOGISTICAL DATA

|                              |              |
|------------------------------|--------------|
| Temperature range at storage | -20...+80 °C |
|------------------------------|--------------|

Energy labelling regulation data acc EU 2019/2015

|                                                      |              |
|------------------------------------------------------|--------------|
| Lighting technology used                             | LED          |
| Non-directional or directional                       | NDLS         |
| Mains or non-mains                                   | MLS          |
| Light source cap-type (or other electric interface)  | E14          |
| Connected light source (CLS)                         | No           |
| Color-tuneable light source                          | No           |
| Envelope                                             | No           |
| High luminance light source                          | No           |
| Anti-glare shield                                    | No           |
| Correlated colour temperature type                   | SINGLE_VALUE |
| Networked standby power for CLS                      | 0 W          |
| Claim of equivalent power                            | Yes          |
| Length                                               | 58.00 mm     |
| Height                                               | 25.00 mm     |
| Width                                                | 25.00 mm     |
| Chromaticity coordinate x                            | 0,313        |
| Chromaticity coordinate y                            | 0.337        |
| R9 Colour rendering index                            | > 0          |
| Beam angle correspondence                            | SPHERE_360   |
| Survival factor                                      | 0,90         |
| Displacement factor                                  | 0.5          |
| LED light source replaces a fluorescent light source | No           |

Oops! An Error Occurred

The server returned a "500 Internal Server Error".

Something is broken. Please let us know what you were doing when this error occurred. We will fix it as soon as possible. Sorry for any inconvenience caused.

The server returned a "500 Internal Server Error".

Something is broken. Please let us know what you were doing when this error occurred. We will fix it as soon as possible. Sorry for any inconvenience caused.

|              |         |
|--------------|---------|
| Model number | AC45898 |
|--------------|---------|

DOWNLOAD DATA

| Documents and certificates                                                        |                               |
|-----------------------------------------------------------------------------------|-------------------------------|
|  | Declarations Of Conformity CE |
| Photometric and lighting design files                                             |                               |
|  | Spectral power distribution   |

LOGISTICAL DATA

| Product code  | Packaging unit (Pieces/Unit) | Dimensions (length x width x height) | Gross weight | Volume                |
|---------------|------------------------------|--------------------------------------|--------------|-----------------------|
| 4099854067020 | Folding box<br>1             | 28 mm x 28 mm x 67 mm                | 17.00 g      | 0.05 dm <sup>3</sup>  |
| 4099854067037 | Shipping box<br>20           | 150 mm x 122 mm x 77 mm              | 376.00 g     | 1.41 dm <sup>3</sup>  |
| 4099854067044 | Shipping box<br>120          | 256 mm x 160 mm x 248 mm             | 2391.00 g    | 10.16 dm <sup>3</sup> |

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

References / Links

- For dimming conformity see [www.ledvance.com/dim](http://www.ledvance.com/dim)
- For Guarantee see [www.ledvance.com/guarantee](http://www.ledvance.com/guarantee)

DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.

Oops! An Error Occurred

The server returned a "500 Internal Server Error".

Something is broken. Please let us know what you were doing when this error occurred. We will fix it as soon as possible. Sorry for any inconvenience caused.