

# PRODUCT DATASHEET

## LS SUP -2000/TW/927-965/5/IP67

LED STRIP SUPERIOR-2000 TW PROTECTED | IP67 protected Tunable White LED strips with 2000 lm/m for professional applications with very good color rendering and lifetime



---

### Areas of application

- Suitable for indoor and outdoor applications (IP67)
- Cove lighting
- Hotels
- Offices
- General illumination

---

### Product benefits

- Great scope of design options due to long and flexible TW LED strips
- Easy installation, no tools required for connection
- Easy mounting thanks to self-adhesive tape
- Maximum flexibility due to large range of accessories
- Simple connection thanks to integrated cables on both sides

---

### Product features

- Adjustable color temperature via Tunable White: 2,700...6,500 K
- Smallest cuttable unit: 100 mm
- Lifetime (L70/B50): up to 50,000 h at  $T_c \text{ max.} \leq 85^\circ\text{C}$
- Dimmable by pulse width modulation (PWM)
- Type of protection: IP67
- Highly UV-resistant
- Salt mist proof



## TECHNICAL DATA

### Electrical data

|                           |                         |
|---------------------------|-------------------------|
| Nominal wattage           | 108.00 W                |
| Construction wattage      | 108.00 W                |
| Nominal wattage per meter | 21.6 W <sup>1)</sup>    |
| Nominal voltage           | 24 V <sup>2)</sup>      |
| Input voltage range       | 23...25 V <sup>2)</sup> |
| Type of current           | DC                      |
| Nominal current           | 4500 mA                 |

1) 10.8W for 2700K, 10.8W for 6500K

2)  $V_{DC}$

### Photometrical data

|                                      |               |
|--------------------------------------|---------------|
| Luminous efficacy                    | 76 lm/W       |
| Luminous flux                        | 8450 lm       |
| Luminous flux per meter              | 1640 lm       |
| Luminous flux per module chain       | 9762 lm       |
| Luminous flux per meter - Warm white | 900 lm/m      |
| Luminous flux per meter - Cool white | 1010 lm/m     |
| Color temperature                    | 2700...6500 K |
| Color rendering index Ra             | > 90          |
| Light color LED                      | Tunable White |
| Light color (designation)            | Tunable White |
| Standard deviation of color matching | <4 sdcm       |

### Light technical data

|                                    |          |
|------------------------------------|----------|
| Beam angle                         | 110 °    |
| Rated beam angle (half peak value) | 110.00 ° |

### LED MODULE INFORMATION

|                                  |     |
|----------------------------------|-----|
| Number of LEDs per meter         | 120 |
| Number of LEDs per module        | 600 |
| Number of LEDs per smallest unit | 6   |

### Dimensions & Weight



|                         |                     |
|-------------------------|---------------------|
| Length                  | 5000.00 mm          |
| Length – smallest unit  | 100 mm              |
| Cable length            | 500.000             |
| Width                   | 12.00 mm            |
| Height                  | 5.00 mm             |
| Prewired                | Yes                 |
| Conductor cross section | 0.5 mm <sup>2</sup> |
| LED pitch               | 16.67 mm            |
| Short pitch             | No                  |
| Product weight          | 440.00 g            |

### Colors & materials

|                |          |
|----------------|----------|
| Cover material | Silicone |
|----------------|----------|

### Temperatures & operating conditions

|                                      |                            |
|--------------------------------------|----------------------------|
| Ambient temperature range            | -20...+55 °C <sup>1)</sup> |
| Maximum temperature at tc test point | 85 °C <sup>2)</sup>        |

<sup>1)</sup> Providing that temperature at Tc point is below max value during operation

<sup>2)</sup> Exceeding the maximum specified ratings can reduce expected life time or destroy the LED strip

### Lifespan

|                        |         |
|------------------------|---------|
| Nominal lamp life time | 50000 h |
|------------------------|---------|

### Capabilities

|                       |                   |
|-----------------------|-------------------|
| Dimmable              | Yes <sup>1)</sup> |
| Lowest bending radius | 30 mm             |
| Self-adhesive         | Yes               |

<sup>1)</sup> Dimmable with suitable drivers, see also [www.ledvance.com/dim](http://www.ledvance.com/dim)

### Certificates & Standards

|                           |                 |
|---------------------------|-----------------|
| Approval marks – approval | CE / TUV / ENEC |
| Protection class          | III             |

|                                          |      |
|------------------------------------------|------|
| Type of protection                       | IP67 |
| Energy class of contained Light source   | G    |
| Salt mist resistance acc. IEC 60068-2-52 | Yes  |
| UV resistance acc. IEC 60068-2-5         | Yes  |

## LOGISTICAL DATA

|                              |              |
|------------------------------|--------------|
| Temperature range at storage | -35...+85 °C |
|------------------------------|--------------|

## DOWNLOAD DATA

| Documents and certificates                                                       |                               |
|----------------------------------------------------------------------------------|-------------------------------|
|  | User instruction              |
|  | Addon Technical Information   |
|  | Declarations Of Conformity CE |

## LOGISTICAL DATA

| Product code  | Packaging unit (Pieces/Unit) | Dimensions (length x width x height) | Gross weight | Volume                |
|---------------|------------------------------|--------------------------------------|--------------|-----------------------|
| 4058075436008 | Folding box<br>1             | 262 mm x 262 mm x 30 mm              | 680.00 g     | 2.06 dm <sup>3</sup>  |
| 4058075436015 | Shipping box<br>10           | 300 mm x 280 mm x 285 mm             | 7271.00 g    | 23.94 dm <sup>3</sup> |
| 4058075436022 | Shipping box<br>20           | 585 mm x 320 mm x 310 mm             | 14205.00 g   | 58.03 dm <sup>3</sup> |

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

## DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.