

# PRODUCT DATASHEET

## LED Value Batten 600 mm 10 W 4000 K

LED VALUE BATTEN | LED batten luminaires for wall and ceiling mounting

---

### Areas of application

- Indoor applications
- Ceiling and wall surface mounting
- Corridors, stairwells, basements
- General indoor illumination



---

### Product benefits

- Excellent price/performance ratio
- High energy savings compared to luminaires that use conventional light sources
- Functional and minimalistic design

---

### Product features

- Replacement for traditional T8 luminaires
- Wall and ceiling batten luminaire
- Material: Aluminium (Housing), Polycarbonate (Diffusor)
- Lifetime: up to 30,000 h
- Color temperature: 4,000 K
- Luminaire efficacy: up to 100 lm/W
- Lengths available: 0.6 m, 1.2 m, 1.5 m



TECHNICAL DATA

Electrical data


|                        |               |
|------------------------|---------------|
| Nominal wattage        | 10.00 W       |
| Nominal voltage        | 220...240 V   |
| Mains frequency        | 50...60 Hz    |
| Nominal current        | 75.000 mA     |
| Power factor $\lambda$ | > 0.5         |
| Protection class       | II            |
| Operating mode         | Mains voltage |

Photometrical data

|                                                |            |
|------------------------------------------------|------------|
| Luminous flux                                  | 1000 lm    |
| Total luminous flux of contained light sources | 1300 lm    |
| Luminous efficacy                              | 100 lm/W   |
| Color temperature                              | 4000 K     |
| Light color (designation)                      | Cool White |
| Color rendering index Ra                       | $\geq 80$  |
| Standard deviation of color matching           | < 6 sdcn   |
| Beam angle                                     | 150 °      |

Dimensions & Weight

|                |           |
|----------------|-----------|
| Length         | 634.00 mm |
| Width          | 29.00 mm  |
| Height         | 44.00 mm  |
| Product weight | 225.00 g  |



Materials & Colors

|               |          |
|---------------|----------|
| Product color | Silver   |
| Housing color | Silver   |
| Body material | Aluminum |

|                 |                    |
|-----------------|--------------------|
| Cover material  | Polycarbonate (PC) |
| Mercury content | 0.0 mg             |

### Application & Mounting

|                           |                 |
|---------------------------|-----------------|
| Ambient temperature range | -20...+40 °C    |
| Type of connection        | Screw terminal  |
| Type of protection        | IP20            |
| Dimmable                  | No              |
| Mounting type             | Surface         |
| Mounting location         | Ceiling / Wall  |
| Application environment   | Indoor          |
| LED module replaceable    | Not replaceable |
| With light source         | Yes             |

### Lifespan

|                            |         |
|----------------------------|---------|
| Lifespan L70/B50 at 25 °C  | 30000 h |
| Number of switching cycles | 100000  |

### Certificates & Standards

|                                                      |                 |
|------------------------------------------------------|-----------------|
| Standards                                            | CE / EAC / UKCA |
| Luminaire with limited surface temperature, "D sign" | No              |

### EQUIPMENT / ACCESSORIES

- Mounting clips included

### DOWNLOAD DATA

| Documents and certificates                                                         |                               |
|------------------------------------------------------------------------------------|-------------------------------|
|  | User instruction              |
|  | Packaging insert              |
|  | Declarations Of Conformity CE |

### LOGISTICAL DATA

| Product code  | Packaging unit (Pieces/Unit) | Dimensions (length x width x height) | Gross weight | Volume                |
|---------------|------------------------------|--------------------------------------|--------------|-----------------------|
| 4058075268142 | Folding box<br>1             | 44 mm x 30 mm x 634 mm               | 234.00 g     | 0.84 dm <sup>3</sup>  |
| 4058075268159 | Shipping box<br>20           | 660 mm x 165 mm x 205 mm             | 5036.00 g    | 22.32 dm <sup>3</sup> |

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

---

## DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.