

PRODUCT DATASHEET SENSOR CEILING FLUSH 360DEG IP20 WT

SENSOR CEILING FLUSH IP20 | Stand-alone motion and light sensors for flush ceiling mounting



Areas of application

- Indoor
- Stairways
- Basement
- Restrooms

Product benefits

- Sensor for optimized energy savings
- Compact design

Product features

- 2 operating modes selectable (light 6h continous on, switch-on by movement)
- Type of protection: IP20
- Protection class: II




TECHNICAL DATA

Electrical data

Nominal voltage	220240 V
Mains frequency	5060 Hz
Protection class	П

Dimensions & Weight

Diameter	83 mm
Height	63.00 mm
Product weight	80.00 g



Materials & Colors

Product color	White
Body material	Polycarbonate (PC)
Mercury content	0.0 mg

Application & Mounting

Ambient temperature range	-20+40 °C	
Temperature range at storage	-25+70 °C	
Type of connection	Screw terminal, 3-Pole	
Type of protection	IP20	
Dimmable	No	
Mounting type	Recessed	
Mounting location	Ceiling	

Lifespan

Lifespan L70/B50 at 25 °C	50000 h

Sensor

Type of sensor	Light / Motion	
Sensor technology	Passive infrared (PIR)	
Sensor detection angle	360 °	
Sensor controlled switching time	2 s15 min	
Detection range of motion sensor	6 m	
Detection threshold of daylight sensor	11000 lx	

Certificates & Standards

Standards CE / EAC / UKCA

DOWNLOAD DATA

	Documents and certificates
PDF	User instruction
PDF	Declarations Of Conformity CE

LOGISTICAL DATA

Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
4058075240315	Folding box 1	90 mm x 90 mm x 72 mm	106.00 g	0.58 dm³
4058075240322	Shipping box 8	190 mm x 190 mm x 160 mm	1163.00 g	5.78 dm ³

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.