

# PRODUCT DATASHEET OTI DALI DIM 1-4CH D

CV Dimmers with DALI | Constant Voltage - Indoor - dimmable



## Areas of application

- Suitable for indoor installations
- Separate installation (ceiling mounting)

#### **Product benefits**

- Very precise dimming thanks to digital light control

## **Product features**


- Intelligent digital dimmer (DALI) with constant output voltage
- Dimming range: 0...100 %
- Device fits also for special applications where dimming below 1 % is required

# **TECHNICAL DATA**

# Electrical data

Nominal wattage	120.00 W
Nominal output power	240 W
Nominal voltage	1248 V
Nominal output voltage	1248 V
Mains frequency	0 Hz
Galvanic isolation	SELV

# **Dimensions & Weight**



Length	181.00 mm
Mounting hole spacing, length	175.5 mm
Width	42.00 mm
Height	20.00 mm
Cable cross-section, input side	0,52,5 mm²
Cable cross-section, output side	0,52,5 mm²
Product weight	86.00 g

## Colors & materials

Casing material	Plastic
Body material	Plastic

# Temperatures & operating conditions

Ambient temperature range	-20+50 °C
Maximum temperature at tc test point	60 °C
Max.housing temperature in case of fault	110 °C
Permitted rel. humidity during operation	585 % <sup>1)</sup>

<sup>1)</sup> Maximum 56 days/year at 85 %

# Lifespan

ECG lifetime 50000 h
----------------------

# **Capabilities**

Dimmable	Yes	
Dimming interface	DALI-2	
Dimming range	0.1100 %	
Overheating protection	Automatic reversible	
No-load proof	Yes	
Short-circuit protection	Automatic reversible	
Suitable for fixtures with prot. class	1/11	
Type of connection, output side	Screw terminal	

## Certificates & Standards

Approval marks – approval	CE / EAC / RCM / ENEC 05	
Standards	Acc. to EC 61347-2-13 / Acc. to EN 62384 / Acc. to EN 55015 / Acc. to EN 61547	
Protection class	Ш	
Type of protection	IP20	

# **LOGISTICAL DATA**

	Temperature range at storage	-40+85 °C
--	------------------------------	-----------

# **DOWNLOAD DATA**

	Documents and certificates
PDF	User instruction
PDF	Declarations Of Conformity CE
	Certificates
PDF	Declarations Of Conformity UKCA

# **LOGISTICAL DATA**

Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
4062172166010	Unpacked 1		86.00 g	
4062172166027	Shipping box 20	229 mm x 197 mm x 133 mm	2088.00 g	6.00 dm <sup>3</sup>

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

## **DISCLAIMER**

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.