

PRODUCT DATASHEET

TRUSYS FLEX P RAIL 1500 5P END WT

TruSys® FLEX ENERGY RAIL 5-POLE | 5-pole mounting rail

Areas of application

- Industry halls, high rack warehouse, hardware stores



Product benefits

- Simple installation
- High flexibility thanks to two available lengths (1500 mm, 3000 mm and 1500 mm end rail)

Product features


- Through wired with 5 core cable
- Different lengths available
- Electrical connection internal at the first luminaire, no external connection unit required
- Steel-sheet housing
- End-Rail without electrical and mechanical connectors



TECHNICAL DATA

Dimensions & Weight

Length	1500 mm
Width	70.2 mm
Height	38.8 mm
Product weight	1450.00 g



Materials & Colors

Product color	White
Body material	Steel

Application & Mounting

Mounting location	Ceiling
With light source	No

Certificates & Standards

Standards	CE / CB / UKCA / ENEC / EAC
-----------	-----------------------------

EQUIPMENT / ACCESSORIES

– Various accessories available

DOWNLOAD DATA

Documents and certificates



User instruction



Declarations Of Conformity CE



Declarations Of Conformity UKCA

CAD/BIM files



BIM_Revit_3D



CAD_STEP_3D

Tender texts



Tender documents

LOGISTICAL DATA

Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
4058075781733	Sleeve 1	43 mm x 52 mm x 1,680 mm	1462.00 g	3.76 dm ³
4058075781740	Shipping box 4	1,570 mm x 191 mm x 141 mm	6844.00 g	42.13 dm ³

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.