

PRODUCT DATASHEET

Orbis Dublin 490 mm 36W 830 SI

ORBIS DUBLIN | LED ceiling luminaires with plastic ring



Areas of application

- Indoor applications
- Kitchens, living rooms, children's rooms or home offices

Product benefits

- Very homogenous light
- Elegant design

Product features

- Decorative domestic lighting
- Ceiling luminaire with advanced LED technology



TECHNICAL DATA

Electrical data


Nominal wattage	36.00 W
Nominal voltage	220...240 V
Mains frequency	50...60 Hz
Nominal current	160.000 mA
Max. no. of lum. on circuit break. B16 A	50
Max. no. of lum. on circuit break. C16 A	66
Power factor λ	> 0.90
Total harmonic distortion	< 13 %
Protection class	I
Operating mode	Electronic control gear (ECG)

Photometrical data

Luminous flux	2800 lm
Total luminous flux of contained light sources	4700 lm
Luminous efficacy	77 lm/W
Color temperature	3000 K
Light color (designation)	Warm White
Color rendering index Ra	≥ 80
Standard deviation of color matching	≤ 6 sdcm
Flickering metric (Pst LM)	< 1
Stroboscope effect metric (SVM)	< 0.4
Photobiological safety group acc. to EN62778	RG0
Photobiological safety group acc. to EN62471	RG0
Beam angle	120 °

Dimensions & Weight

Diameter	487.00 mm
Height	78.00 mm
Product weight	1200.00 g



Materials & Colors

Product color	Silver
Housing color	Silver
Body material	Metal
Cover material	Plastic
Glow Wire Test according to IEC 60695-2-12	650 °C

Application & Mounting

Ambient temperature range	-20...+40 °C
Temperature range at storage	-20...+80 °C
Type of connection	Terminal, 3-Pole (L, N, PE)
Type of protection	IP20
Dimmable	No
Mounting type	Surface
Application environment	Indoor
LED module replaceable	Not replaceable
With light source	Yes

Lifespan

Lifespan L70/B50 at 25 °C	50000 h
Number of switching cycles	25000

Certificates & Standards

Standards	CE / UKCA
Luminaire with limited surface temperature, "D sign"	No

Additional product data

Product remark	Available from September 2023
Number of illuminants	1

DOWNLOAD DATA

Documents and certificates	
	User instruction

Documents and certificates	
	Packaging insert
	Declarations Of Conformity CE
	Declarations Of Conformity UKCA

LOGISTICAL DATA

Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
4058075829282	Folding box 1	85 mm x 505 mm x 505 mm	1635.00 g	21.68 dm ³
4058075829299	Shipping box 4	525 mm x 360 mm x 525 mm	7769.00 g	99.23 dm ³

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.