

PRODUCT DATASHEET

Orbis Paris 500 mm 3XE27 BW

ORBIS PARIS | Socketed ceiling luminaires with fabric ring



Areas of application

- Indoor applications
- Kitchens, living rooms, children's rooms or home offices

Product benefits

- Replaceable LED lamp
- Elegant design

Product features

- Decorative domestic lighting
- Ceiling luminaire with socket
- Fabric material



TECHNICAL DATA

Electrical data

Nominal voltage	220...240 V
Mains frequency	50...60 Hz
Protection class	I
Operating mode	Mains voltage

Dimensions & Weight

Diameter	480.00 mm
Height	105.00 mm
Product weight	910.00 g



Materials & Colors

Product color	Brown
Housing color	Brown
Body material	Steel TC fabric PVC
Cover material	Polystyrene (PS)
Glow Wire Test according to IEC 60695-2-12	650 °C
Mercury content	0.0 mg

Application & Mounting

Ambient temperature range	-20...+40 °C
Temperature range at storage	-20...+80 °C
Type of connection	Terminal, 3-Pole (L, N, PE)
Type of protection	IP20
Dimmable	No
Mounting type	Surface
Application environment	Indoor
With light source	No

Certificates & Standards

Standards	CE / UKCA
Luminaire with limited surface temperature, "D sign"	No

Additional product data

Product remark	Available from September 2023
----------------	-------------------------------

DOWNLOAD DATA

Documents and certificates	
	User instruction
	Packaging insert
	Declarations Of Conformity CE
	Declarations Of Conformity UKCA

LOGISTICAL DATA

Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
4058075829084	Folding box 1	112 mm x 492 mm x 492 mm	1435.00 g	27.11 dm ³
4058075829091	Shipping box 4	506 mm x 506 mm x 475 mm	6885.00 g	121.62 dm ³

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.