

PRODUCT DATASHEET DALI magic

DALI magic | USB to DALI programming interface



Areas of application

- Configuration of DALI ECG functions
- Monitoring of DALI installations

Product benefits

DALI wizard software features (included)

- Intuitive configuration of up to 64 DALI electronic control gears
- Offline / Online configuration of DALI installations
- "DALI-Spy"-functionality for recording DALI line data flow

Tuner4TRONIC software features

- Programming of OSRAM ECG
- Suitable for the shop floor environments
- Performs fast manual and automatic programming
- Easily enables the use of the pre-parameterization service

Product features

- USB DALI converter for Tuner4TRONIC and DALI wizard software for Windows PC
- Pushbutton to test DALI dimming without need of connection to computer
- Powered by USB or by included universal power supply
- Integrated automatic DALI supply of up to 64 devices (up to 4 if powered by USB)

TECHNICAL DATA

Electrical data

Nominal wattage	7.00 W
Nominal voltage	220240 V
Mains frequency	50/60 Hz

Dimensions & Weight

Length	120.0 mm
Width	120.00 mm
Height	28.00 mm
Product weight	370.00 g

Colors & materials

Temperatures & operating conditions

Ambient temperature range	+15+50 °C
,	

Capabilities

Dimmable	Yes
Dimming interface	DALI

Certificates & Standards

Protection class	1
Type of protection	IP20

EQUIPMENT / ACCESSORIES

- Universal power supply (100...240 V_{AC} , 5.9 V_{DC} , 1.15 A, EU plug)
- USB cable (male A to male B), 180 cm
- Bipolar plug for DALI connection

DOWNLOAD DATA

	Documents and certificates
POF	User instruction
PDF	Declarations Of Conformity CE

LOGISTICAL DATA

Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
4052899039551	Shipping box 1	148 mm x 98 mm x 135 mm	376.00 g	1.96 dm³

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

References / Links

- Compatible software available at www.ledvance.com/software

DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.