

# PRODUCT DATASHEET

## Cabinet LED Corner Sensor 350mm Two Light

Cabinet LED Corner | Low voltage undercabinet luminaires for corner application

---

### Areas of application

- Shelf and undercabinet lighting



---

### Product benefits

- Low voltage luminaire for DC operation with external driver
- Suitable for mounting in corners
- Homogenous light distribution
- Easy and fast mounting on nearly every surface (adhesive tape or screws)

---

### Product features

- Luminous flux: up to 480 lm
- Switch on and off by movements with 5 cm distance in front of the infrared motion sensor
- Stepless dimming by covering the infrared motion sensor in 5 cm distance for at least one second
- Material: aluminum
- Color: silver
- Available in two lengths: 35 cm and 55 cm



- Available as single and double luminaire kit

TECHNICAL DATA

Electrical data


|                                          |                     |
|------------------------------------------|---------------------|
| Nominal wattage                          | 9.00 W              |
| Nominal voltage                          | 220...240 V         |
| Mains frequency                          | 50...60 Hz          |
| Nominal current                          | 90.000 mA           |
| Max. no. of lum. on circuit break. B16 A | -                   |
| Max. no. of lum. on circuit break. C10 A | -                   |
| Max. no. of lum. on circuit break. C16 A | -                   |
| Power factor $\lambda$                   | > 0.5               |
| Protection class                         | II                  |
| Operating mode                           | External LED driver |

Photometrical data

|                                                |               |
|------------------------------------------------|---------------|
| Luminous flux                                  | 640 lm        |
| Total luminous flux of contained light sources | 800 lm        |
| Luminous efficacy                              | 71 lm/W       |
| Color temperature                              | 3000 K        |
| Light color (designation)                      | Warm White    |
| Color rendering index Ra                       | $\geq 80$     |
| Standard deviation of color matching           | $\leq 6$ sdcm |
| Photobiological safety group acc. to EN62778   | RG1           |
| Photobiological safety group acc. to EN62471   | RG0           |
| Beam angle                                     | 110 °         |

Dimensions & Weight

|                |           |
|----------------|-----------|
| Length         | 350.00 mm |
| Width          | 40.70 mm  |
| Height         | 23.00 mm  |
| Product weight | 423.00 g  |
| Cable length   | 1500 mm   |



## Materials & Colors

|                 |                          |
|-----------------|--------------------------|
| Product color   | Gray                     |
| Housing color   | Gray                     |
| Body material   | Polycarbon Acrylonitrile |
| Cover material  | Polycarbonate (PC)       |
| Mercury content | 0.0 mg                   |

## Application & Mounting

|                                        |                    |
|----------------------------------------|--------------------|
| Ambient temperature range              | -20...+40 °C       |
| Temperature range at storage           | -30...+70 °C       |
| Type of connection                     | Plug type C (EU)   |
| Type of protection                     | IP20               |
| Protection class IK (shock resistance) | IK03               |
| Dimmable                               | Yes                |
| Mounting type                          | Surface            |
| Mounting location                      | Cabinet undersides |
| Application environment                | Indoor             |
| LED module replaceable                 | Not replaceable    |
| With light source                      | Yes                |

## Lifespan

|                            |         |
|----------------------------|---------|
| Lifespan L70/B50 at 25 °C  | 30000 h |
| Number of switching cycles | 100000  |

## Sensor

|                                  |                    |
|----------------------------------|--------------------|
| Type of sensor                   | Motion             |
| Sensor technology                | Infrared/Photocell |
| Detection range of motion sensor | 5 cm               |

## Certificates & Standards

|                                                      |          |
|------------------------------------------------------|----------|
| Standards                                            | CE / EAC |
| Luminaire with limited surface temperature, "D sign" | No       |

---

## EQUIPMENT / ACCESSORIES

- External mains adapter (cable length: 1.5 m) included

## DOWNLOAD DATA

## Documents and certificates



User instruction



Packaging insert



Declarations Of Conformity CE

## LOGISTICAL DATA

| Product code  | Packaging unit (Pieces/Unit) | Dimensions (length x width x height) | Gross weight | Volume                |
|---------------|------------------------------|--------------------------------------|--------------|-----------------------|
| 4058075227910 | Folding box<br>1             | 94 mm x 71 mm x 400 mm               | 493.00 g     | 2.67 dm <sup>3</sup>  |
| 4058075227927 | Shipping box<br>8            | 416 mm x 303 mm x 205 mm             | 4317.00 g    | 25.84 dm <sup>3</sup> |

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

## DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.