


PRODUCT DATASHEET

FL MAX LUM P 600W 757 SYM 60 WAL

FLOODLIGHT MAX 600W LUMINAIRE HEAD | High-power floodlight for large area and sports lighting, up to 82 klm



Areas of application

- Outdoor use (IP66)
- Lighting of large areas
- Sports facilities
- Construction areas
- Direct replacement for luminaires using HID lamps

Product benefits

- Very bright, robust and durable
- Energy savings of up to 45 % compared to luminaires that use conventional discharge lamps
- Easy dimming to 50% by wiring
- No upper light output ratio (ULOR 0%) when mounted at 0° tilt
- Optimized product logistic, luminaire heads and power supplies to be ordered separately in stand-alone packaging
- Low flicker light
- 5 years guarantee

Product features

- Modular, high-power floodlight with up to 135 lm/W
- Joint or separate installation with Floodlight Max power supply with up to 40 m distance
- Available with 10°, 30° and 60° symmetric beam angles, as well as 50°x110° asymmetric light distribution
- Mounting bracket for up to 180° tilting
- Highly-transparent, tempered glass diffuser




TECHNICAL DATA

Electrical data

Nominal wattage	600.00 W
Nominal voltage	180 V
Nominal current	3160 mA
Operating mode	External LED driver

Photometrical data

Luminous flux	80500 lm
Luminous efficacy	134 lm/W
Color temperature	5700 K
Light color (designation)	Cool Daylight
Color rendering index Ra	≥70
Standard deviation of color matching	< 5 sdc _{cm}
Luminous intensity	-
Low flicker	Yes
Flickering metric (Pst LM)	-
Stroboscope effect metric (SVM)	-
Photobiological safety group acc. to EN62778	RG2
Beam angle	60 °



Dimensions & Weight

Length	472.00 mm
Width	591.00 mm
Height	279.00 mm

Product weight	15800.00 g
Cable length	1300 mm

Materials & Colors

Product color	White aluminum
Housing color	White aluminum
Body material	Aluminum
Cover material	Glass
Light emitting surface material	Glass
Glow Wire Test according to IEC 60695-2-12	650 °C
Mercury content	0.0 mg

Application & Mounting

Ambient temperature range	-30...+50 °C
Temperature range at storage	-40...+70 °C
Type of connection	Terminal, 3-Pole (L, N, PE)
Type of protection	IP66
Protection class IK (shock resistance)	IK08
Dimmable	No
Mounting type	Surface
Mounting location	Wall / Pole / Floor
Application environment	Outdoor
Adjustable	Yes
LED module replaceable	Not replaceable
With light source	Yes

Lifespan

Lifespan L70/B50 at 25 °C	100000 h
Lifespan L80/B10 at 25 °C	75000 h
Lifespan L90/B10 at 25 °C	50000 h
Number of switching cycles	100000

Certificates & Standards

Standards	CE / CB / ENEC / EAC
Luminaire with limited surface temperature, "D sign"	No
Ball shot safe	No

EQUIPMENT / ACCESSORIES

- Power supply not included in luminaire head delivery unit
- Operation only with official 600 W power supply, GTIN(EAN) 4058075580718
- Aiming device in preparation
- Visor for front light cut-off in preparation

Safety advice


- Floodlight Max Luminaire Heads must be operated with official Floodlight Max Power Supplies only, as described in the user manual.
- If only one fixation point is used for luminaires installed higher >3m, a secondary fixation of luminaire and bracket (e.g. a restraining wire) is needed for safety reasons.
- The luminaire should be positioned so that prolonged staring into the luminaire at a distance closer than 4 m is not expected.

DOWNLOAD DATA

Documents and certificates	
	User instruction
	Addon Technical Information
	Packaging insert
	Declarations Of Conformity CE
	Declarations Of Conformity UKCA
Photometric and lighting design files	
	IES file (IES)
	LDT file (Eulumdat)
	ULD file (DIALux)
	ROLF file (RELUX)

Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
4058075580602	Shipping box 1	619 mm x 619 mm x 238 mm	15800.00 g	91.19 dm³

ADDITIONAL CATALOG INFORMATION



LDV FL MAX											
	S/g 0°	30°	60°	90°							
600 W	S1 0.12 m	0.17 m	0.22 m	0.25 m	<75 kg	832	230 VAC	DW	3	4	8
	S2 0.30 m	0.30 m	0.23 m	0.18 m							
	S3 0.28 m	0.28 m	0.28 m	0.28 m							
	S4 0.12 m	0.22 m	0.28 m	0.28 m							
900 W	S1 0.14 m	0.19 m	0.21 m	0.22 m	<100 kg	1	1	2	2	5	
	S2 0.44 m	0.41 m	0.31 m	0.12 m							
	S3 0.13 m	0.12 m	0.12 m	0.12 m							
	S4 0.13 m	0.17 m	0.28 m	0.27 m							
1200 W	S1 0.15 m	0.20 m	0.21 m	0.22 m	<135 kg	1	1	2	2	4	
	S2 0.50 m	0.47 m	0.37 m	0.12 m							
	S3 0.14 m	0.14 m	0.14 m	0.14 m							
	S4 0.14 m	0.14 m	0.14 m	0.14 m							

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.