

Blacklight BL368 Linear T8 F15W T8 BL368 0000082



Product features

The energy distribution of the BL368 lamp is concentrated around the spectral peak at 368nm which is the most important frequency for the attraction of flying insects.













PRODUCT OVERVIEW

Product name	F15W T8 BL368
Technology	Special applications
Lamp shape	Tubular shape
Туре	T8
Cap/Base	G13
Lamp finish	Frosted/Coated
Fixture rating	Enclosed
General application	SPG
ETIM Class	EC002962
E-number FI	4940737
Light colour	BL368 Blacklight
Wattage (W)	15.00
Dimmable	No
Dimming method	N/A
Average life (Nominal) (h)	14000
Product EAN number	5410288000824

DATA TABLE

General data	
Product name	F15W T8 BL368
Technology	Special applications
Lamp shape	Tubular shape
Туре	T8
Cap/Base	G13
Lamp finish	Frosted/Coated
Fixture rating	Enclosed
General application	SPG
Operating temperature range (°C)	-15°C+40°C
ETIM Class	EC002962
E-number FI	4940737



Blacklight BL368 Linear T8 F15W T8 BL368 0000082

Ambient temperature for maximum luminous flux (°C)	25
Light colour	BL368 Blacklight
Adjustable chromaticity	N
Electrical data	
Wattage (W)	15.00
Current (A)	0.310
Primary Supply/Product voltage - min (V)	46.0
Primary Supply/Product voltage - max (V)	64.0
Control gear required	Yes
Dimmable	No
Dimming method	N/A
Drive current (mA)	310
_ifetime data	
Average life (Nominal) (h)	14000
Physical data	
Nominal Product Length (mm)	450.0
Nominal Product Diameter (mm)	26
Max. Length base to base (mm) - A	437.4
Length base to pin Min-Max (mm) - B	442.1-444.5
Max. Lamp Length (mm) - C/L	451.6
Max. Lamp Diameter (mm) - D	28.0
Weight (kg)	0.063
Packaging	
Single packaging type	Carton
Product EAN number	5410288000824
Packaging single length / height (cm)	45.2
Packaging single width (cm)	2.9
Packaging single depth (cm)	2.8
DUN14 (outer)	15410288000821
Units per outer package	25
Packaging outer length / height (cm)	48.0
Packaging outer width (cm)	15.5
Packaging outer depth (cm)	15.0
Safety data	
Lamp mercury content (mg)	9.0
Optimal operating condition (°C)	-15-40
Opumai operating continuon (C)	
Breakage elegating instructions	Applicable
Breakage cleaning instructions	
Breakage cleaning instructions Recommendation for disposal at end of life	Applicable
Recommendation for disposal at end of	




Blacklight BL368 Linear T8 F15W T8 BL368 0000082

Suitable for household illumination

No

Safety message Not suitable for household

PHOTOMETRY



TECHNICAL DRAWINGS

