



Spot Performer 3C Compact

- High performance compact track spot with high luminous efficiency and homogeneous light distribution
- Various beam angles achievable with exchangeable reflectors
- Fitting common Global/Nordic Aluminum® 3C Tracks – and many other standard types
- Low glare due to matte black anti-glare ring
- Honeycomb filters available for further glare reduction




Specifications

Item Code	Item Description	Equivalent to (W)	Power (W)	Lumen	Luminaire efficacy	CCT (K)	Weight (kg/pc)
541001095400	LEDSpot3C-C-P 37W-BLE-4000-36D-BL	HID 50W	37	3360	120	4000	0.95

Accessories



550098000300
LEDSpot3C-C-P R85-Reflector-24D



599007082900
LEDSpot3C-C-P R85-Honeycomb

Packaging Information

Item			Box			
Item Code	Item Description	EU HS Code	Dimensions (mm) (LxWxH)	Gross Weight (kg)	EAN	pc/box
541001095400	LEDSpot3C-C-P 37W-BLE-4000-36D-BL	94051190	285x120x240	1.18	6941408872650	1
140063563	LEDSmartlight-Rc-Sensor	85365005	100x100x70	0.19	6956321862602	1
140063564	LEDSmartlight-Switch	85365005	89x21x101	0.10	6956321862619	1
506006003100	LEDSmart-Relay-500W	85364900	37x110x57	0.10	6956321820824	1
550098000300	LEDSpot3C-C-P R85-Reflector-24D	94059200	75x75x40	0.05	6941408820910	1
560000005700	Smart Connect Box	85176200	100x60x105	0.30	6941497711663	1
560000008400	LEDSmartlight-Rc-MW-Sensor	85365005	110x110x75	0.19	6941497726995	1
560098000600	LEDSmart-Sensor Surface-Module-WH	94059200	330x220x255	0.15	6941497703972	1
599007082900	LEDSpot3C-C-P R85-Honeycomb	94059200	82x82x12.8	0.16	6941408896717	1
821017001100	LEDSmart-BLE-Multi-Switch-Module	94059200	46x46x30	0.07	6941408898476	1

Technical Specifications	
Lifetime (L70)	70,000 h
Lifetime (L80)	50,000 h
On-/Off-cycles	100,000
Colour consistency (SDCM)	4
Dimmability	BLE
Beam angle	36°
Maximum tilt angle	85°
Finishing	Matte Black
Colour rendering index (CRI)	> 90
Degree of protection (IP)	IP20
Impact strength	IK02 (BLE)
Protection class	II (BLE)
Risk group (EN 62471)	RG1
With control gear	Yes
Glow wire test	650°C
Power factor	≥ 0.9

Electrical Supply	
Frequency	50/60 Hz
Nominal voltage	220-240 V
DC input voltage	See catalogue appendix
	Connection Specifications

Mechanical Properties	
Housing material	Aluminium
Optical material	Aluminum
Lens material	Polycarbonate

Ambient Conditions	
Operating temperature	-10~+45°C
Application temperature	+25°C
Storage environment	-25~+50°C



ENERGY

OPPLÉ Lighting
 541001095400

A

B

C

D

E

F

G

F

37

kWh/1000h

2019/2015

Dimensional Drawing (mm)

Photometric Data

