





- Compact Bluetooth® presence detector for use in OPPLE Smart Lighting System
- Large detection area of \emptyset 20m
- Very easy to set up with the OPPLE Smart Lighting App, or Smart Connect Box through the web user interface
- Suitable for high ceiling applications (max detection height of 13m)
- Adjustable detection area for low/high ceiling applications
- Complete wireless communication via Bluetooth® Low Energy (BLE)





Specifications

Item Code	Item Description	Sensor range
560000008400	LEDSmartlight-Rc-MW-Sensor	20 m

Accessories





















560006001000 LEDSmart-Sensor IP65-Module Excluding sensor

Technical Specifications		
IP-class	IP20 / IP65*	
IK-class	IK02 / IK07*	
Finishing	White RAL9003	
Communication	Opple Bluetooth® Low Energy Mesh	
Protection Class	II	
Detection diameter (when installed at 2.5-13m height)	Max Ø 20m	
Detection angle	360°	
Detection technology	Microwave (MW)	
Switch-off delay time	1min-60min	
Daylight balance	No	
Temperature sensor	No	
Humidity sensor	No	

^{*} Only in combination with IP65 assessory modules

Electrical Supply	
Power consumption	2.2W
Nominal voltage	220-240 V AC
Frequency	50/60 Hz




Ambient conditions	
Operating Temperature	-30~+55°C







Dimensional drawing (mm)




560000008400 - LEDSmartlight-Rc-MW-Sensor




560098000600 - LEDSmart-Sensor Surface-Module-WH






560006000900 - LEDSmart-Sensor IP65-Base-Module




560006001000 - LEDSmart-Sensor IP65-Module


Detection range




Installation opening drawing (mm)




Recommended Height (m)	Sensitivity Setting	Detection Radius (m)
3	Low	7
8	Middle	9
9	High	10
12	High	7



Installation - Low Ceiling Suggested installation height 3m



Installation - Medium Ceiling Suggested installation height 8m



Installation - High Ceiling Suggested installation height 9-12m

