



Filament

- Classic light bulb shape ensures an easy replacement
- Instant 100% light when switched on and no startup time
- No UV / IR radiance so there is less risk of damage




Specifications

Item Code	Item Description	Equivalent to (W)	Power (W)	Lumen	Efficacy (lm/W)	CCT (K)	Weight (kg/pc)
B35, On-Off							
500011000500	LED-E-B35-FILA-E14-2.8W-2700K-CL	GLS 25W		250	89	2700	0.01


Packaging Information

Item			Box			
Item Code	Item Description	EU HS Code	Dimensions (mm) (LxWxH)	Gross Weight (kg)	EAN	pc/box
500011000500	LED-E-B35-FILA-E14-2.8W-2700K-CL	85395200	45x45x100	0.04	6945730433220	1

Technical Specifications		Electrical Supply	
Lifetime (L70)	15,000 h	Frequency	50/60 Hz
On-/Off-cycles	100,000	Nominal voltage	220-240 V
Dimmability	On-Off	DC input voltage	No
Beam angle	360°	Ambient Conditions	
Finishing	Clear	Operating temperature	-20~+40°C
Colour rendering index (CRI)	> 80	Application temperature	+25°C
		Storage environment	-25~+50°C



Dimensional Drawing (mm)



Photometric Data

