

Obico 80
OBICO IP65 740LM 2CCT DIM ADJ WHT
0005350



- Product features**
- Integrated LED recessed spotlight, 2-axis adjustable (horizontal rotation 360°, vertical tilt 30°)
RAL9016 white bezel colour, two temperature light colors selectable: 3000K, 4000K. Lumen output 740lm (4000K), 8.5W, dimmable trailing/leading edge, 38° degree beam angle, aluminium and steel body, low profile 40mm recessed depth, IP65 frontal degree, IK03, loop-in/loop-out terminals for fast wiring, 96mm bezel diameter, 80mm cutout, clear lens.

PRODUCT OVERVIEW

Product name	OBICO IP65 740LM 2CCT DIM ADJ WHT
Technology	LED
Cap/Base	N/A
Housing	Aluminium
Mount	Ceiling recessed mounting
General application	Hospitality
ETIM Class	EC001744
E-number FI	4278283
Warranty	5 years
Fixture luminous flux (lm)	740
Luminaire efficacy (lm/W)	87
Light colour	Neutral White
CRI (Ra)	80
Colour Variation Initial (SDCM)	SDCM6
Beam Angle (°)	38
Photobiological Risk Group	RG1
Total power consumption (W)	8.5
Electrical protection	Class II
Control gear type	LED driver constant current
Dimmable	Yes
Dimming method	Mains: leading / trailing edge
Housing colour	White
IP rating	IP65/20
IK rating	IK03
Product EAN number	5410288053509

DATA TABLE

General data	
Product name	OBICO IP65 740LM 2CCT DIM ADJ WHT
Technology	LED
Cap/Base	N/A
Housing	Aluminium
Mount	Ceiling recessed mounting
General application	Hospitality
Operating temperature range (°C)	-20°C...+40°C

Obico 80

OBICO IP65 740LM 2CCT DIM ADJ WHT

0005350

Performance ambient temperature Tq (°C)	25
ETIM Class	EC001744
E-number FI	4278283
Warranty	5 years

Optical data

Fixture luminous flux (lm)	740
Luminaire efficacy (lm/W)	87
Correlated colour temperature range (K)	3000 - 4000
Light colour	Neutral White
CRI (Ra)	80
Colour Variation Initial (SDCM)	SDCM6
Beam Angle (°)	38
Distribution type	Symmetric
Photobiological Risk Group	RG1

Electrical data

Total power consumption (W)	8.5
Lamp power factor	0.9
THD (at 230 V, 50 Hz, full load, at 100% dimming level) xx.x %	25
Electrical protection	Class II
Control gear type	LED driver constant current
Dimmable	Yes
Dimming method	Mains: leading / trailing edge
Drive current (mA)	185
Inrush Current (A)	2
Inrush Duration (µs)	20
Glow Wire Test (°C)	650
Energy Efficiency Class (A->G) of contained light source	D
Nominal Frequency (Hz)	50/60Hz
Max. products per 10A C Breaker	90
Max. products per 13A C Breaker	118
Max. products per 16A C Breaker	145
Max. products per 20A C Breaker	181
Max. products per 10A B Breaker	90
Max. products per 13A B Breaker	118
Max. products per 16A B Breaker	145
Max. products per 20A B Breaker	181
Connectable conductor cross section - Min (mm²)	0.75
Connectable conductor cross section - Max (mm²)	1.5

Lifetime data

Lifespan L70 B50	88000
Lifespan L80 B20	52000
Lifespan L90 B10	24000

Obico 80

OBICO IP65 740LM 2CCT DIM ADJ WHT

0005350

Physical data

Housing colour	White
IP rating	IP65/20
IK rating	IK03
Diffuser finish	Other
Diffuser material	None
Reflector finish	None
Nominal Product Height (mm)	40
Nominal Product Diameter (mm)	96
Cutout Dimensions (W x L in mm or Diameter in mm)	80
Weight (kg)	0.248

Packaging

Single packaging type	Carton
Product EAN number	5410288053509
Packaging single length / height (cm)	13.1
Packaging single width (cm)	8.0
Packaging single depth (cm)	14.4
DUN14 (inner)	25410288053503
Units per inner package	4
Packaging inner length / height (cm)	30.1
Packaging inner width (cm)	17.2
Packaging inner depth (cm)	14.6
DUN14 (outer)	15410288053506
Units per outer package	24
Packaging outer length / height (cm)	36.5
Packaging outer width (cm)	32.5
Packaging outer depth (cm)	46.6

Safety data

Optimal operating condition (°C)	-20-40
----------------------------------	--------

PHOTOMETRY

TECHNICAL DRAWINGS

