



Product features

PRODUCT OVERVIEW

| nology Ind | candescent |
|-----------------------------|--|
| illology | candescent |
| (Rated) (W) 15 | 5 |
| o shape Ot | ther |
| Py | ygmy Clear |
| Base E | 14 |
| o finish CI | lear |
| re rating O _I | pen |
| eral application Ho | ospitality, Residential & Consumer, Retail |
| I Class Ed | C000014 |
| mber FI 47 | 741158 |
| anty 2 | years |
| nous flux (lm) 11 | 10 |
| ur temperature (K) 25 | 500 |
| colour | omelight |
| (Ra) 10 | 00 |
| ur Variation Initial (SDCM) | /A |
| obiological Risk Group No | ot applicable |
| age (W) 15 | |
| nable Ye | es |
| ning method Ma | ains: leading / trailing edge |
| age life (Nominal) (h) 10 | 000 |
| uct EAN number 54 | 110288080741 |

DATA TABLE

| General data | |
|---------------------|---|
| Product name | Pigmy Oven lamp 15w 22mm 230-240V SLV |
| Technology | Incandescent |
| Watt (Rated) (W) | 15 |
| Lamp shape | Other |
| Туре | Pygmy Clear |
| Cap/Base | E14 |
| Lamp finish | Clear |
| Fixture rating | Open |
| General application | Hospitality, Residential & Consumer, Retail |



| ETIM Class | EC000014 |
|---|--------------------------------|
| E-number FI | 4741158 |
| Warranty | 2 years |
| Optical data | |
| Luminous flux (lm) | 110 |
| Luminous flux (Rated) (Im) | 90 |
| Colour temperature (K) | 2500 |
| Light colour | Homelight |
| CRI (Ra) | 100 |
| Colour Variation Initial (SDCM) | N/A |
| Adjustable chromaticity | N |
| Photobiological Risk Group | Not applicable |
| Electrical data | |
| Wattage (W) | 15 |
| Starting time (max) (s) | 0.01 |
| Warm-up time to 60% of full light (max) | Instant full light |
| (s) | |
| Primary Supply/Product voltage - min (V) | 230 |
| Primary Supply/Product voltage - max (V) | 240 |
| Lamp power factor | 1 |
| Control gear required | No |
| No. Of switching cycles before premature failures | >4000 |
| Dimmable | Yes |
| Dimming method | Mains: leading / trailing edge |
| Lamp Energy Label (class) | G |
| kWh per 1000 hours burning time | 15 |
| | |
| Lifetime data | |
| Average life (Nominal) (h) | 1000 |
| Average life (Rated) (h) | 1000 |
| | |
| Physical data | |
| Nominal Product Length (mm) | 48 |
| Nominal Product Diameter (mm) | 22 |
| Max. Lamp Length (mm) - C/L | 49 |
| Max. Lamp Diameter (mm) - D | 23 |
| Weight (kg) | 0.009 |
| | |
| Packaging | |
| Single packaging type | Carton |
| Product EAN number | 5410288080741 |
| Packaging single length / height (cm) | 9.0 |
| Packaging single width (cm) | 5.0 |
| Packaging single depth (cm) | 2.5 |
| DUN14 (outer) | 15410288080748 |
| Units per outer package | 14 |
| | |



Packaging outer length / height (cm)12.8Packaging outer width (cm)19.0Packaging outer depth (cm)10.0


Safety data

| Breakage cleaning instructions | Not applicable |
|--|----------------------------|
| Recommendation for disposal at end of life | Not Applicable |
| Special purpose lamp | Yes |
| Suitable for household illumination | No |
| Safety message | Not suitable for household |

PHOTOMETRY

TECHNICAL DRAWINGS





15 kWh/1000h





