

Resisto Throughwiring  
Resisto 1500 IP66 4200lm 840 5xTH  
0010251



- Product features**
- Resisto, integrated LED weatherproof luminaire, with UV stabilized flat diffuser designed to achieve uniform lit appearance, optimise light output and to reduce glare. 301 stainless steel diffuser clips and fixing brackets for surface mounting. Polycarbonate housing and diffuser - no yellow discolouration over time. 4200lm; 30W; 140lm/W; 4000K; SDCM<5; non dimmable; CRI80; IP66; IK08; Class I; 69,000hrs (L80B20) lifespan; 1500mm x 89mm x 88mm; D-mark; through wiring.

PRODUCT OVERVIEW

|                                 |                                                           |
|---------------------------------|-----------------------------------------------------------|
| Product name                    | Resisto 1500 IP66 4200lm 840 5xTH                         |
| Technology                      | LED                                                       |
| Cap/Base                        | N/A                                                       |
| Housing                         | PC Polycarbonate                                          |
| Mount                           | Ceiling surface mounting, Suspended, Wall surface mounted |
| General application             | Logistics & Industry                                      |
| ETIM Class                      | EC002892                                                  |
| E-number FI                     | 4357062                                                   |
| Warranty                        | 5 years                                                   |
| Fixture luminous flux (lm)      | 4200                                                      |
| Luminaire efficacy (lm/W)       | 140                                                       |
| Colour temperature (K)          | 4000                                                      |
| CRI (Ra)                        | 80                                                        |
| Colour Variation Initial (SDCM) | SDCM5                                                     |
| Colour Consistency (SDCM)       | 5                                                         |
| Beam Angle (°)                  | 110                                                       |
| Glare control                   | < 23                                                      |
| Photobiological Risk Group      | RG1                                                       |
| Total power consumption (W)     | 30                                                        |
| Electrical protection           | Class I                                                   |
| Control gear type               | LED driver constant current                               |
| Dimmable                        | No                                                        |
| Dimming method                  | N/A                                                       |
| LED Flickering Rate             | Ultra low (5% or less)                                    |
| Housing colour                  | Grey                                                      |
| IP rating                       | IP66                                                      |
| IK rating                       | IK08                                                      |
| Product EAN number              | 5410288102511                                             |

DATA TABLE

|              |                                   |
|--------------|-----------------------------------|
| General data |                                   |
| Product name | Resisto 1500 IP66 4200lm 840 5xTH |
| Technology   | LED                               |
| Cap/Base     | N/A                               |
| Housing      | PC Polycarbonate                  |

## Resisto Throughwiring

*Resisto 1500 IP66 4200lm 840 5xTH*

0010251

|                                                     |                                                           |
|-----------------------------------------------------|-----------------------------------------------------------|
| Mount                                               | Ceiling surface mounting, Suspended, Wall surface mounted |
| General application                                 | Logistics & Industry                                      |
| Operating temperature range (°C)                    | -20°C...+40°C                                             |
| Performance ambient temperature T <sub>q</sub> (°C) | 25                                                        |
| ETIM Class                                          | EC002892                                                  |
| E-number FI                                         | 4357062                                                   |
| Warranty                                            | 5 years                                                   |

### Optical data

|                                 |         |
|---------------------------------|---------|
| Fixture luminous flux (lm)      | 4200    |
| Luminaire efficacy (lm/W)       | 140     |
| Colour temperature (K)          | 4000    |
| CRI (Ra)                        | 80      |
| Colour Variation Initial (SDCM) | SDCM5   |
| Colour Consistency (SDCM)       | 5       |
| Beam Angle (°)                  | 110     |
| Distribution type               | Diffuse |
| Glare control                   | < 23    |
| Photobiological Risk Group      | RG1     |

### Electrical data

|                                                                |                             |
|----------------------------------------------------------------|-----------------------------|
| Total power consumption (W)                                    | 30                          |
| Primary Supply/Product voltage - min (V)                       | 220                         |
| Primary Supply/Product voltage - max (V)                       | 240                         |
| Lamp power factor                                              | 1                           |
| THD (at 230 V, 50 Hz, full load, at 100% dimming level) xx.x % | 20                          |
| Electrical protection                                          | Class I                     |
| Control gear type                                              | LED driver constant current |
| No. Of switching cycles before premature failures              | >50000                      |
| Dimmable                                                       | No                          |
| Dimming method                                                 | N/A                         |
| Drive current (mA)                                             | 350                         |
| Inrush Current (A)                                             | 5.5                         |
| Inrush Duration (µs)                                           | 20                          |
| Glow Wire Test (°C)                                            | 850                         |
| Energy Efficiency Class (A->G) of contained light source       | D                           |
| Nominal Frequency (Hz)                                         | 50/60Hz                     |
| LED Flickering Rate                                            | Ultra low (5% or less)      |
| Max. products per 10A C Breaker                                | 41                          |
| Max. products per 13A C Breaker                                | 53                          |
| Max. products per 16A C Breaker                                | 65                          |
| Max. products per 20A C Breaker                                | 82                          |
| Max. products per 10A B Breaker                                | 41                          |
| Max. products per 13A B Breaker                                | 53                          |
| Max. products per 16A B Breaker                                | 65                          |
| Max. products per 20A B Breaker                                | 82                          |

Resisto Throughwiring  
Resisto 1500 IP66 4200lm 840 5xTH  
0010251

Connectable conductor cross section - 2.5  
Max (mm²)

Lifetime data

|                  |        |
|------------------|--------|
| Lifespan L70 B50 | 100000 |
| Lifespan L80 B20 | 69000  |
| Lifespan L90 B10 | 31000  |

Physical data

|                             |                  |
|-----------------------------|------------------|
| Housing colour              | Grey             |
| IP rating                   | IP66             |
| IK rating                   | IK08             |
| Diffuser finish             | Frosted          |
| Diffuser material           | PC Polycarbonate |
| Nominal Product Length (mm) | 1500             |
| Nominal Product Width (mm)  | 87               |
| Nominal Product Height (mm) | 80               |
| Weight (kg)                 | 2.1              |


Packaging

|                                       |                |
|---------------------------------------|----------------|
| Single packaging type                 | Carton         |
| Product EAN number                    | 5410288102511  |
| Packaging single length / height (cm) | 150.5          |
| Packaging single width (cm)           | 10.0           |
| Packaging single depth (cm)           | 8.5            |
| DUN14 (outer)                         | 05410288102511 |
| Units per outer package               | 1              |
| Packaging outer length / height (cm)  | 150.5          |
| Packaging outer width (cm)            | 10.0           |
| Packaging outer depth (cm)            | 8.5            |

Safety data

|                                  |        |
|----------------------------------|--------|
| Optimal operating condition (°C) | -20-40 |
|----------------------------------|--------|

PHOTOMETRY





## Resisto Throughwiring

*Resisto 1500 IP66 4200lm 840 5xTH*

0010251

---

### TECHNICAL DRAWINGS

---