

Eco Linear Double Ended R7s
DE 78MM ECO 230V 48W R7S BL
0022572



- Product features
- Instant illumination, - Excellent colour rendering, - Sparkling light output, - Transformer free operation, - Average life 1500hours, - Suitable for outdoor floodlighting/security lighting, - Suitable for interior floodlighting, uplighting and wall washing.

PRODUCT OVERVIEW

Product name	DE 78MM ECO 230V 48W R7S BL
Technology	Halogen
Watt (Rated) (W)	48
Lamp shape	Tube, double-ended
Type	Halogen
Cap/Base	R7s
Lamp finish	Clear
Fixture rating	Enclosed
General application	Education, Hospitality, Logistics & Industry, Museums & Galleries, Office, Residential & Consumer, Retail
ETIM Class	EC000038
Warranty	2 years
Luminous flux (lm)	700
Colour temperature (K)	2900
Light colour	Homelight
CRI (Ra)	100
Colour Variation Initial (SDCM)	N/A
Photobiological Risk Group	Not applicable
Wattage (W)	48
Dimmable	Yes
Dimming method	Mains: leading / trailing edge
Average life (Nominal) (h)	1500
Product EAN number	5410288225722

DATA TABLE

General data	
Product name	DE 78MM ECO 230V 48W R7S BL
Technology	Halogen
Watt (Rated) (W)	48
Lamp shape	Tube, double-ended
Type	Halogen
Cap/Base	R7s
Lamp finish	Clear
Fixture rating	Enclosed

Eco Linear Double Ended R7s

DE 78MM ECO 230V 48W R7S BL

0022572

General application	Education, Hospitality, Logistics & Industry, Museums & Galleries, Office, Residential & Consumer, Retail
ETIM Class	EC000038
Warranty	2 years

Optical data

Luminous flux (lm)	700
Luminous flux (Rated) (lm)	700
Colour temperature (K)	2900
Light colour	Homelight
CRI (Ra)	100
Colour Variation Initial (SDCM)	N/A
Adjustable chromaticity	N
Photobiological Risk Group	Not applicable

Electrical data

Wattage (W)	48
Equivalent watt (W)	60
Starting time (max) (s)	0.01
Warm-up time to 60% of full light (max) (s)	Instant full light
Primary Supply/Product voltage - min (V)	230
Primary Supply/Product voltage - max (V)	230
Lamp power factor	1
Control gear required	No
No. Of switching cycles before premature failures	>10000
Dimmable	Yes
Dimming method	Mains: leading / trailing edge
Lamp Energy Label (class)	G
kWh per 1000 hours burning time	48

Lifetime data

Average life (Nominal) (h)	1500
Average life (Rated) (h)	1500

Physical data

Nominal Product Length (mm)	80.3
Nominal Product Diameter (mm)	12
Max. Lamp Length (mm) - C/L	81
Max. Lamp Diameter (mm) - D	12
Weight (kg)	0.005

Packaging


Single packaging type	Mix blister(20% carton, 80% pl)
Product EAN number	5410288225722
Packaging single length / height (cm)	14.0
Packaging single width (cm)	12.0
Packaging single depth (cm)	1.2

Eco Linear Double Ended R7s
DE 78MM ECO 230V 48W R7S BL
0022572

DUN14 (outer)	15410288225729
Units per outer package	10
Packaging outer length / height (cm)	14.9
Packaging outer width (cm)	14.5
Packaging outer depth (cm)	12.4

Safety data	
Breakage cleaning instructions	N/A
Recommendation for disposal at end of life	Not Applicable
Special purpose lamp	No
Suitable for household illumination	Yes
Safety message	None

PHOTOMETRY




TECHNICAL DRAWINGS

Eco Linear Double Ended R7s
DE 78MM ECO 230V 48W R7S BL
0022572



SYLVANIA

0022572




48
kWh/1000h



Eco Linear Double Ended R7s
DE 78MM ECO 230V 48W R7S BL
0022572


SYLVANIA
0022572



48
kWh/1000h

