

Blacklight BL368 Compact Lynx-L 36W BL368

0025710



Product features

These BL368 tubes emit an upgraded highly concentrated radiation with peak around 368nm. Flying insect - eye sensitivity is generally at or near this frequency100% improvement in effectiveness (at 368nm)Depreciation of UV-A output over time is significantly reduced (80% at 5000hrs of original 100















PRODUCT OVERVIEW

Product name	Lynx-L 36W BL368
Technology	Special applications
Lamp shape	U shape
Туре	Compact
Cap/Base	2G11
Lamp finish	Frosted/Coated
Fixture rating	Enclosed
General application	SPG
ETIM Class	EC002962
E-number FI	4940710
Light colour	BL368 Blacklight
Photobiological Risk Group	RG0
Wattage (W)	36
Dimmable	No
Dimming method	N/A
Average life (Nominal) (h)	15000
Product EAN number	5410288257105

DATA TABLE

General data	
Product name	Lynx-L 36W BL368
Technology	Special applications
Lamp shape	U shape
Туре	Compact
Cap/Base	2G11
Lamp finish	Frosted/Coated
Fixture rating	Enclosed



Blacklight BL368 Compact Lynx-L 36W BL368 0025710

General application	SPG
Operating temperature range (°C)	-15°C+50°C
ETIM Class	EC002962
E-number FI	4940710
E-Hullibel FI	4940710
Optical data	
Light colour	BL368 Blacklight
Adjustable chromaticity	N
Photobiological Risk Group	RG0
Electrical data	
Wattage (W)	36
Primary Supply/Product voltage - min (V)	230
Primary Supply/Product voltage - max (V)	240
Control gear required	Yes
Dimmable	No
Dimming method	N/A
Lifetime data	
Average life (Nominal) (h)	15000
Physical data	
Nominal Product Height (mm)	404
Nominal Product Diameter (mm)	44
Weight (kg)	0.095
Packaging	
	O-d
Single packaging type	Carton
Product EAN number	5410288257105
Packaging single length / height (cm)	42.53
Packaging single length / height (cm) Packaging single width (cm)	42.53 4.63
Packaging single length / height (cm) Packaging single width (cm) Packaging single depth (cm)	42.53 4.63 2.37
Packaging single length / height (cm) Packaging single width (cm) Packaging single depth (cm) DUN14 (outer)	42.53 4.63 2.37 15410288257102
Packaging single length / height (cm) Packaging single width (cm) Packaging single depth (cm) DUN14 (outer) Units per outer package	42.53 4.63 2.37 15410288257102 10
Packaging single length / height (cm) Packaging single width (cm) Packaging single depth (cm) DUN14 (outer) Units per outer package Packaging outer length / height (cm)	42.53 4.63 2.37 15410288257102 10 44.6
Packaging single length / height (cm) Packaging single width (cm) Packaging single depth (cm) DUN14 (outer) Units per outer package Packaging outer length / height (cm) Packaging outer width (cm)	42.53 4.63 2.37 15410288257102 10 44.6 14.0
Packaging single length / height (cm) Packaging single width (cm) Packaging single depth (cm) DUN14 (outer) Units per outer package Packaging outer length / height (cm)	42.53 4.63 2.37 15410288257102 10 44.6
Packaging single length / height (cm) Packaging single width (cm) Packaging single depth (cm) DUN14 (outer) Units per outer package Packaging outer length / height (cm) Packaging outer width (cm) Packaging outer depth (cm)	42.53 4.63 2.37 15410288257102 10 44.6 14.0
Packaging single length / height (cm) Packaging single width (cm) Packaging single depth (cm) DUN14 (outer) Units per outer package Packaging outer length / height (cm) Packaging outer width (cm) Packaging outer depth (cm)	42.53 4.63 2.37 15410288257102 10 44.6 14.0
Packaging single length / height (cm) Packaging single width (cm) Packaging single depth (cm) DUN14 (outer) Units per outer package Packaging outer length / height (cm) Packaging outer width (cm) Packaging outer depth (cm) Safety data	42.53 4.63 2.37 15410288257102 10 44.6 14.0
Packaging single length / height (cm) Packaging single width (cm) Packaging single depth (cm) DUN14 (outer) Units per outer package Packaging outer length / height (cm) Packaging outer width (cm) Packaging outer depth (cm) Safety data Lamp mercury content (mg) Optimal operating condition (°C)	42.53 4.63 2.37 15410288257102 10 44.6 14.0 10.0
Packaging single length / height (cm) Packaging single width (cm) Packaging single depth (cm) DUN14 (outer) Units per outer package Packaging outer length / height (cm) Packaging outer width (cm) Packaging outer depth (cm) Safety data Lamp mercury content (mg)	42.53 4.63 2.37 15410288257102 10 44.6 14.0 10.0
Packaging single length / height (cm) Packaging single width (cm) Packaging single depth (cm) DUN14 (outer) Units per outer package Packaging outer length / height (cm) Packaging outer width (cm) Packaging outer depth (cm) Safety data Lamp mercury content (mg) Optimal operating condition (°C) Breakage cleaning instructions Recommendation for disposal at end of	42.53 4.63 2.37 15410288257102 10 44.6 14.0 10.0 3.5 -15-50 Applicable
Packaging single length / height (cm) Packaging single width (cm) Packaging single depth (cm) DUN14 (outer) Units per outer package Packaging outer length / height (cm) Packaging outer width (cm) Packaging outer depth (cm) Safety data Lamp mercury content (mg) Optimal operating condition (°C) Breakage cleaning instructions Recommendation for disposal at end of life	42.53 4.63 2.37 15410288257102 10 44.6 14.0 10.0 3.5 -15-50 Applicable Applicable
Packaging single length / height (cm) Packaging single width (cm) Packaging single depth (cm) DUN14 (outer) Units per outer package Packaging outer length / height (cm) Packaging outer width (cm) Packaging outer depth (cm) Safety data Lamp mercury content (mg) Optimal operating condition (°C) Breakage cleaning instructions Recommendation for disposal at end of life Special purpose lamp	42.53 4.63 2.37 15410288257102 10 44.6 14.0 10.0 3.5 -15-50 Applicable Applicable Yes



Blacklight BL368 Compact Lynx-L 36W BL368 0025710

TECHNICAL DRAWINGS

