


## RefLED PAR20 RefLED RETRO PAR20 DIM 540LM 830 36° SL 0028269

#### **Product features**

- High performance LED PAR lamps with the same look and feel of traditional PAR lamps
- Glass construction means no colours clashing between the lamp and fixture
- Reduced visible heatsink from the front
- Mercury-free solution
- Lower maintenance cost
- Lifetime: up to 25,000 hours
- High lumen efficacy
- Dimmable on approved dimmers\*
- 3 year warranty
- Suitable for general lighting and accent lighting for hotels, restaurants, bars, lobbies, corridors and halls



### PRODUCT OVERVIEW

Product name	RefLED RETRO PAR20 DIM 540LM 830 36° SL
Technology	LED
Watt (Rated) (W)	8
Cap/Base	E27
Fixture rating	Open
General application	Hospitality, Museums & Galleries, Residential & Consumer, Retail
ETIM Class	EC001959
E-number FI	4740795
Warranty	3 years
Colour temperature (K)	3000
Light colour	Warm White
CRI (Ra)	80
Colour Variation Initial (SDCM)	SDCM6
Colour Consistency (SDCM)	6
Beam Angle (°)	36
Wattage (W)	8
Dimmable	Yes
Average life (Nominal) (h)	25000
Product EAN number	5410288282695

### **DATA TABLE**

General data	
Product name	RefLED RETRO PAR20 DIM 540LM 830 36° SL
Technology	LED
Watt (Rated) (W)	8
Cap/Base	E27
Fixture rating	Open
General application	Hospitality, Museums & Galleries, Residential & Consumer, Retail
Performance ambient temperature Tq (°C)	25
ETIM Class	EC001959



## RefLED PAR20

# RefLED RETRO PAR20 DIM 540LM 830 36° SL **0028269**

E accept on El	4740705
E-number FI	4740795
Warranty	3 years
Optical data	
Colour temperature (K)	3000
Light colour	Warm White
CRI (Ra)	80
Colour Variation Initial (SDCM)	SDCM6
Colour Consistency (SDCM)	6
Luminous Intensity (cd)	1200
Beam Angle (°)	36
beam Angle ( )	30
Electrical data	
Wattage (W)	8
Starting time (max) (s)	<0.5
Warm-up time to 60% of full light (max) (s)	<0.5
Lamp power factor	0.9
No. Of switching cycles before premature failures	>50000
Dimmable	Yes
Nominal Frequency (Hz)	50/60Hz
Lifetime data	
Average life (Nominal) (h)	25000
Average life (Rated) (h)	25000
Physical data	
Nominal Product Length (mm)	89
Nominal Product Diameter (mm)	64
Weight (kg)	0.14
Wolght (kg)	0.11
Packaging	
Single packaging type	Carton
Product EAN number	5410288282695
Packaging single length / height (cm)	10.8
Packaging single width (cm)	6.8
Packaging single depth (cm)	6.8
DUN14 (outer)	15410288282692
Units per outer package	6
Packaging outer length / height (cm)	22.7
Packaging outer width (cm)	16.8
Packaging outer depth (cm)	15.1
Safety data	
Breakage cleaning instructions	Not applicable
Special purpose lamp	No
Dry applications use only	Yes
Suitable for household illumination	Yes



## RefLED PAR20 RefLED RETRO PAR20 DIM 540LM 830 36° SL 0028269

Safety messageDimmable with approved dimmersSafety messageNot Suitable for totally enclosed fixtures