

RefLED ES50
RefLED ES50 V6 450LM 830 110d SL
0029181



- Product features
- Compact, energy efficient and exceptional value LED GU10 lamp
 - Same shape and size as halogen GU10 lamp
 - Compact Cluster SMD technology enabling high efficiency with halogen look
 - Reduced visible heat sink from the front
 - Available in 110 degree beam angle
 - High lumen efficacy
 - 15,000 hours average rated life
 - 3 years warranty

PRODUCT OVERVIEW

Product name	RefLED ES50 V6 450LM 830 110d SL
Technology	LED
Watt (Rated) (W)	6.2
Type	LED exchangeable
Cap/Base	GU10
Fixture rating	Open
General application	Office, Hospitality, Retail, Education, Residential & Consumer, Museums & Galleries
ETIM Class	EC001959
E-number FI	4741067
Warranty	3 years
Colour temperature (K)	3000
Light colour	Warm White
CRI (Ra)	80
Colour Variation Initial (SDCM)	SDCM6
Colour Consistency (SDCM)	6
Beam Angle (°)	110
Photobiological Risk Group	RG1
Wattage (W)	6.2
Dimmable	No
Average life (Nominal) (h)	15000
Product EAN number	5410288291819

DATA TABLE

General data	
Product name	RefLED ES50 V6 450LM 830 110d SL
Technology	LED
Watt (Rated) (W)	6.2
Type	LED exchangeable
Cap/Base	GU10
Fixture rating	Open
General application	Office, Hospitality, Retail, Education, Residential & Consumer, Museums & Galleries
Operating temperature range (°C)	-20°C...+40°C

RefLED ES50

RefLED ES50 V6 450LM 830 110d SL

0029181

Performance ambient temperature Tq (°C)	25
ETIM Class	EC001959
E-number FI	4741067
Warranty	3 years

Optical data

Colour temperature (K)	3000
Light colour	Warm White
CRI (Ra)	80
Colour Variation Initial (SDCM)	SDCM6
Colour Consistency (SDCM)	6
Luminous Intensity (cd)	250
Beam Angle (°)	110
Photobiological Risk Group	RG1
Lumen maintenance at end of nominal life (%)	70

Electrical data

Wattage (W)	6.2
Equivalent watt (W)	60
Primary Supply/Product voltage - min (V)	220
Primary Supply/Product voltage - max (V)	240
Control gear required	No
No. Of switching cycles before premature failures	>50000
Dimmable	No
Inrush Current (A)	3.65
Inrush Duration (µs)	4200
Lamp Energy Label (class)	F
Nominal Frequency (Hz)	50/60Hz
Max. products per 16A C Breaker	123
Max. products per 16A B Breaker	74

Lifetime data

Lifespan L70 B50	15000
Average life (Nominal) (h)	15000
Average life (Rated) (h)	15000

Physical data

Nominal Product Height (mm)	54
Nominal Product Diameter (mm)	50
Weight (kg)	0.035

Packaging

Single packaging type	Carton
Product EAN number	5410288291819
Packaging single length / height (cm)	8.2
Packaging single width (cm)	6.1

RefLED ES50
RefLED ES50 V6 450LM 830 110d SL
0029181

Packaging single depth (cm)	5.1
DUN14 (inner)	25410288291813
Units per inner package	6
Packaging inner length / height (cm)	9.2
Packaging inner width (cm)	16.4
Packaging inner depth (cm)	13.1
DUN14 (outer)	15410288291816
Units per outer package	60
Packaging outer length / height (cm)	20.8
Packaging outer width (cm)	17.8
Packaging outer depth (cm)	68.5

Safety data

Optimal operating condition (°C)	-20-40
Breakage cleaning instructions	Not applicable
Special purpose lamp	No
Dry applications use only	Yes
Suitable for household illumination	Yes
Safety message	Not Suitable for totally enclosed fixtures

PHOTOMETRY


TECHNICAL DRAWINGS

RefLED ES50
RefLED ES50 V6 450LM 830 110d SL
0029181

**ENERG**

SYLVANIA

0029181




7
kWh/1000h



2019/2015

RefLED ES50
RefLED ES50 V6 450LM 830 110d SL
0029181



7
kWh/1000h



2019/2015