

OptiClip Accessories
OPTICLIP LIGHT E 840 1DC WH
0044035



- Product features
- OPTICLIP LIGHT E 840 1DC WH LED light module with reflector, assembled with 1DC connector, 200-450mA drive current, up to 1970lm flux @450mA drive current, CRI80, 4000K, SDCM 3

PRODUCT OVERVIEW

Product name	OPTICLIP LIGHT E 840 1DC WH
Technology	LED
Cap/Base	N/A
Mount	Ceiling recessed mounting
General application	Education, Office
ETIM Class	EC000996
Warranty	5 years
Fixture luminous flux (lm)	1970
Colour temperature (K)	4000
Light colour	Neutral White
CRI (Ra)	80
Colour Variation Initial (SDCM)	SDCM5
Beam Angle (°)	80
Photobiological Risk Group	RG1
Total power consumption (W)	15
Electrical protection	Class III
Control gear type	LED driver constant current
Dimmable	No
Dimming method	N/A
IP rating	IP20
IK rating	IK07
Product EAN number	5410288440354

DATA TABLE

General data	
Product name	OPTICLIP LIGHT E 840 1DC WH
Technology	LED
Cap/Base	N/A
Mount	Ceiling recessed mounting
General application	Education, Office
Operating temperature range (°C)	-20°C...+40°C
Performance ambient temperature Tq (°C)	25
ETIM Class	EC000996
Warranty	5 years

OptiClip Accessories

OPTICLIP LIGHT E 840 1DC WH
0044035

Optical data

Fixture luminous flux (lm)	1970
Colour temperature (K)	4000
Light colour	Neutral White
CRI (Ra)	80
Colour Variation Initial (SDCM)	SDCM5
Luminous Intensity (cd)	1010
Beam Angle (°)	80
Distribution type	Symmetric
Photobiological Risk Group	RG1

Electrical data

Total power consumption (W)	15
Primary Supply/Product voltage - min (V)	33
Primary Supply/Product voltage - max (V)	38
Electrical protection	Class III
Control gear required	Yes
Control gear type	LED driver constant current
Dimmable	No
Dimming method	N/A
Drive current - Range (mA)	200mA / 450mA
Glow Wire Test (°C)	650
Energy Efficiency Class (A->G) of contained light source	E
Nominal Frequency (Hz)	N/A

Lifetime data

Lifespan L70 B50	100000
Lifespan L70 B20	100000
Lifespan L80 B50	100000
Lifespan L80 B20	100000
Lifespan L80 B10	80000
Lifespan L90 B50	70000
Lifespan L90 B20	60000
Lifespan L90 B10	60000

Physical data

IP rating	IP20
IK rating	IK07
Reflector finish	White
Nominal Product Length (mm)	490
Nominal Product Width (mm)	39
Nominal Product Height (mm)	14
Cutout Dimensions (W x L in mm or Diameter in mm)	482.4x34.4
Weight (kg)	0.23



OptiClip Accessories

OPTICLIP LIGHT E 840 1DC WH

0044035

Packaging	
Single packaging type	Plastic
Product EAN number	5410288440354
Packaging single length / height (cm)	65.0
Packaging single width (cm)	7.0
Packaging single depth (cm)	3.0
DUN14 (outer)	15410288440351
Units per outer package	30
Packaging outer length / height (cm)	57.0
Packaging outer width (cm)	32.0
Packaging outer depth (cm)	24.0
Safety data	
Optimal operating condition (°C)	-20-40
Dry applications use only	No

PHOTOMETRY