

Start Surface Wall Round

START Surface Wall Round IP54 500lm Direct 2CCT

0047134



Product features

- Round shaped exterior surface wall light with integrated LED, RAL9005 - Black Aluminium housing, light emission on one side, 500/480 lm, 6.7 W, 75/72 lm/W, 3000 or 4000K adjustable CCT, non dimmable, CRI>80, 220-240V, Class I, lifespan L70:B50: 90000 hrs IP54, IK07, 76 x 129 x 110mm (W x H x D). Weight: 0.55 kg.



PRODUCT OVERVIEW

| | |
|---------------------------------|---|
| Product name | START Surface Wall Round IP54 500lm Direct 2CCT |
| Technology | LED |
| Cap/Base | N/A |
| Housing | Aluminium |
| Mount | Wall recessed, Wall surface mounted |
| General application | Residential & Consumer |
| ETIM Class | EC002892 |
| E-number FI | 4579601 |
| Warranty | 5 years |
| Fixture luminous flux (lm) | 500 |
| Luminaire efficacy (lm/W) | 75 |
| Light colour | Warm White or Neutral White |
| CRI (Ra) | 80 |
| Colour Variation Initial (SDCM) | SDCM3 |
| Beam Angle (°) | 40 |
| Photobiological Risk Group | RG1 |
| Total power consumption (W) | 6.7 |
| Electrical protection | Class I |
| Control gear type | LED driver constant current |
| Dimmable | No |
| Dimming method | N/A |
| Housing colour | RAL 9005 - Jet black |
| IP rating | IP54 |
| IK rating | IK07 |
| Product EAN number | 5410288471341 |

DATA TABLE

General data

| | |
|--------------|---|
| Product name | START Surface Wall Round IP54 500lm Direct 2CCT |
| Technology | LED |
| Cap/Base | N/A |
| Housing | Aluminium |

Start Surface Wall Round

START Surface Wall Round IP54 500lm Direct 2CCT

0047134

| | |
|----------------------------------|-------------------------------------|
| Mount | Wall recessed, Wall surface mounted |
| General application | Residential & Consumer |
| Operating temperature range (°C) | -20°C...+40°C |
| ETIM Class | EC002892 |
| E-number FI | 4579601 |
| Warranty | 5 years |

Optical data

| | |
|---|-----------------------------|
| Fixture luminous flux (lm) | 500 |
| Luminaire efficacy (lm/W) | 75 |
| Correlated colour temperature range (K) | 3000 - 4000 |
| Light colour | Warm White or Neutral White |
| CRI (Ra) | 80 |
| Colour Variation Initial (SDCM) | SDCM3 |
| Luminous Intensity (cd) | 803 |
| Beam Angle (°) | 40 |
| Distribution type | Symmetric |
| Photobiological Risk Group | RG1 |

Electrical data

| | |
|--|-----------------------------|
| Total power consumption (W) | 6.7 |
| Primary Supply/Product voltage - min (V) | 220 |
| Primary Supply/Product voltage - max (V) | 240 |
| Lamp power factor | 1 |
| THD (at 230 V, 50 Hz, full load, at 100% dimming level) xx.x % | 46 |
| Electrical protection | Class I |
| Control gear type | LED driver constant current |
| Dimmable | No |
| Dimming method | N/A |
| Glow Wire Test (°C) | 650 |
| Energy Efficiency Class (A->G) of contained light source | E |
| Nominal Frequency (Hz) | 50/60Hz |
| Max. products per 10A C Breaker | 70 |
| Max. products per 13A C Breaker | 86 |
| Max. products per 16A C Breaker | 100 |
| Max. products per 20A C Breaker | 100 |
| Max. products per 10A B Breaker | 56 |
| Max. products per 13A B Breaker | 68 |
| Max. products per 16A B Breaker | 82 |
| Max. products per 20A B Breaker | 96 |
| Connectable conductor cross section - Max (mm²) | 1.5 |

Lifetime data

| | |
|------------------|-------|
| Lifespan L70 B50 | 90000 |
| Lifespan L70 B20 | 80000 |
| Lifespan L70 B10 | 78000 |

Start Surface Wall Round

START Surface Wall Round IP54 500lm Direct 2CCT
0047134

| | |
|------------------|-------|
| Lifespan L80 B50 | 56000 |
| Lifespan L80 B20 | 50000 |
| Lifespan L80 B10 | 49000 |
| Lifespan L90 B50 | 27000 |
| Lifespan L90 B20 | 24000 |
| Lifespan L90 B10 | 24000 |

Physical data

| | |
|-----------------------------|----------------------|
| Housing colour | RAL 9005 - Jet black |
| IP rating | IP54 |
| IK rating | IK07 |
| Diffuser finish | Transparent |
| Diffuser material | Glass |
| Nominal Product Length (mm) | 110 |
| Nominal Product Width (mm) | 76 |
| Nominal Product Height (mm) | 127 |
| Weight (kg) | 0.552 |


Packaging

| | |
|---------------------------------------|----------------|
| Single packaging type | Carton |
| Product EAN number | 5410288471341 |
| Packaging single length / height (cm) | 13.5 |
| Packaging single width (cm) | 12.0 |
| Packaging single depth (cm) | 8.0 |
| DUN14 (outer) | 15410288471348 |
| Units per outer package | 8 |
| Packaging outer length / height (cm) | 34.0 |
| Packaging outer width (cm) | 25.5 |
| Packaging outer depth (cm) | 15.5 |

Safety data

| | |
|----------------------------------|--------|
| Optimal operating condition (°C) | -20-40 |
|----------------------------------|--------|

PHOTOMETRY



Start Surface Wall Round

START Surface Wall Round IP54 500lm Direct 2CCT

0047134

TECHNICAL DRAWINGS

