

START Downlight Flat IP44 Dimmable 205mm Round Recessed

Start Downlight Flat 205 IP44 1750LM 840 DIM
0054123



- Product features
- START Downlight Flat IP44 DIM is an integrated LED recessed downlight with a separate, phase dimmable driver and loop in- out box, 17W; 1750Lm; 103Lm/W; 4000K; IP44 rated from the front.

PRODUCT OVERVIEW

Product name	Start Downlight Flat 205 IP44 1750LM 840 DIM
Technology	LED
Cap/Base	N/A
Housing	Aluminium
Mount	Ceiling recessed mounting
General application	Hospitality
ETIM Class	EC001744
E-number FI	4278499
Warranty	5 years
Fixture luminous flux (lm)	1750
Luminaire efficacy (lm/W)	103
Colour temperature (K)	4000
Light colour	Cool White
CRI (Ra)	80
Colour Variation Initial (SDCM)	SDCM3
Beam Angle (°)	120
Glare control	< 28
Photobiological Risk Group	RG0
Total power consumption (W)	17
Electrical protection	Class II
Control gear type	LED driver constant current
Dimmable	Yes
Dimming method	Mains: leading / trailing edge
LED Flickering Rate	Ultra low (5% or less)
Housing colour	RAL 9003 - Signal white
IP rating	IP44/20
IK rating	IK06
Product EAN number	5410288541235

DATA TABLE

General data

Product name	Start Downlight Flat 205 IP44 1750LM 840 DIM
Technology	LED
Cap/Base	N/A
Housing	Aluminium

START Downlight Flat IP44 Dimmable 205mm Round Recessed

Start Downlight Flat 205 IP44 1750LM 840 DIM
0054123

Mount	Ceiling recessed mounting
General application	Hospitality
Operating temperature range (°C)	-20°C...+40°C
Performance ambient temperature Tq (°C)	25
ETIM Class	EC001744
E-number FI	4278499
Warranty	5 years

Optical data

Fixture luminous flux (lm)	1750
Luminaire efficacy (lm/W)	103
Colour temperature (K)	4000
Light colour	Cool White
CRI (Ra)	80
Colour Variation Initial (SDCM)	SDCM3
Beam Angle (°)	120
Distribution type	Symmetric
Glare control	< 28
Photobiological Risk Group	RG0

Electrical data

Total power consumption (W)	17
Primary Supply/Product voltage - min (V)	220
Primary Supply/Product voltage - max (V)	240
Lamp power factor	0.9
THD (at 230 V, 50 Hz, full load, at 100% dimming level) xx.x %	20.0
Electrical protection	Class II
Control gear required	No
Control gear type	LED driver constant current
Dimmable	Yes
Dimming method	Mains: leading / trailing edge
Drive current (mA)	450
Inrush Current (A)	4.16
Inrush Duration (µs)	112
Glow Wire Test (°C)	650
Energy Efficiency Class (A->G) of contained light source	D
Nominal Frequency (Hz)	50Hz
LED Flickering Rate	Ultra low (5% or less)
Max. products per 10A C Breaker	67
Max. products per 13A C Breaker	87
Max. products per 16A C Breaker	107
Max. products per 20A C Breaker	133
Max. products per 10A B Breaker	67
Max. products per 13A B Breaker	87
Max. products per 16A B Breaker	107
Max. products per 20A B Breaker	133

START Downlight Flat IP44 Dimmable 205mm Round Recessed

Start Downlight Flat 205 IP44 1750LM 840 DIM
0054123

Connectable conductor cross section - Min (mm²)	0.75
---	------

Connectable conductor cross section - Max (mm²)	1.5
---	-----

Lifetime data

Lifespan L70 B50	78000
------------------	-------

Lifespan L80 B20	43000
------------------	-------

Lifespan L80 B10	42000
------------------	-------

Lifespan L90 B10	23000
------------------	-------

Physical data

Housing colour	RAL 9003 - Signal white
----------------	-------------------------

IP rating	IP44/20
-----------	---------

IK rating	IK06
-----------	------

Diffuser finish	Opal
-----------------	------

Diffuser material	PS Polystyrene
-------------------	----------------

Reflector finish	None
------------------	------

Nominal Product Height (mm)	21
-----------------------------	----

Nominal Product Diameter (mm)	226
-------------------------------	-----

Cutout Dimensions (W x L in mm or Diameter in mm)	205
---	-----

Weight (kg)	0.546
-------------	-------

Packaging

Single packaging type	Carton
-----------------------	--------

Product EAN number	5410288541235
--------------------	---------------

Packaging single length / height (cm)	25.3
---------------------------------------	------

Packaging single width (cm)	5.0
-----------------------------	-----

Packaging single depth (cm)	23.3
-----------------------------	------

DUN14 (outer)	15410288541232
---------------	----------------

Units per outer package	10
-------------------------	----

Packaging outer length / height (cm)	53.3
--------------------------------------	------

Packaging outer width (cm)	27.3
----------------------------	------

Packaging outer depth (cm)	26.1
----------------------------	------

Safety data

Optimal operating condition (°C)	-20-40
----------------------------------	--------

PHOTOMETRY

TECHNICAL DRAWINGS