


SylFire GU10 - IP65 Fixed  
SylFire GU10 IP65 Fixed WHT  
0059778



Product features

- Recessed fire rated housing frame to use with RefLED GU10 spotlight lamp Ø50mm - GU10 spotlight not included. Steel body, round bezel ring in white RAL9016 finish, fixed (not adjustable), IP65 (frontal) degree of protection, class II, outer dimensions (including wiring box): Ø88\*122mm, cut-out Ø72mm. Fire rated 30, 60, 90 minutes. Suitable for internal environment only.



PRODUCT OVERVIEW

|                       |                                  |
|-----------------------|----------------------------------|
| Product name          | SylFire GU10 IP65 Fixed WHT      |
| Technology            | LED/Halogen                      |
| General application   | Residential & Consumer           |
| ETIM Class            | EC001744                         |
| Warranty              | 3 years                          |
| Light colour          | N/A                              |
| Light source included | Fixture without Lightsource      |
| Electrical protection | Class II                         |
| Housing colour        | RAL 9016 - Traffic white / Bezel |
| IP rating             | IP65/20                          |
| IK rating             | IK03                             |
| Product EAN number    | 5410288597782                    |

DATA TABLE

General data

|                     |                             |
|---------------------|-----------------------------|
| Product name        | SylFire GU10 IP65 Fixed WHT |
| Technology          | LED/Halogen                 |
| General application | Residential & Consumer      |
| ETIM Class          | EC001744                    |
| Warranty            | 3 years                     |

Optical data

|              |     |
|--------------|-----|
| Light colour | N/A |
|--------------|-----|

Electrical data

|                                          |                             |
|------------------------------------------|-----------------------------|
| Light source included                    | Fixture without Lightsource |
| Primary Supply/Product voltage - min (V) | 220                         |
| Primary Supply/Product voltage - max (V) | 240                         |
| Electrical protection                    | Class II                    |
| Nominal Frequency (Hz)                   | 50/60Hz                     |

SylFire GU10 - IP65 Fixed  
*SylFire GU10 IP65 Fixed WHT*  
0059778

|                                                 |      |
|-------------------------------------------------|------|
| Connectable conductor cross section - Min (mm²) | 0.75 |
| Connectable conductor cross section - Max (mm²) | 1.5  |

Physical data

|                                                   |                                  |
|---------------------------------------------------|----------------------------------|
| Housing colour                                    | RAL 9016 - Traffic white / Bezel |
| IP rating                                         | IP65/20                          |
| IK rating                                         | IK03                             |
| Nominal Product Height (mm)                       | 122                              |
| Nominal Product Diameter (mm)                     | 88                               |
| Cutout Dimensions (W x L in mm or Diameter in mm) | 72                               |
| Weight (kg)                                       | 0.254                            |
| Recessed Depth (mm)                               | 122                              |

Packaging

|                                       |                |
|---------------------------------------|----------------|
| Single packaging type                 | Carton         |
| Product EAN number                    | 5410288597782  |
| Packaging single length / height (cm) | 12.0           |
| Packaging single width (cm)           | 10.0           |
| Packaging single depth (cm)           | 13.5           |
| DUN14 (outer)                         | 15410288597789 |
| Units per outer package               | 40             |
| Packaging outer length / height (cm)  | 62.0           |
| Packaging outer width (cm)            | 29.0           |
| Packaging outer depth (cm)            | 42.0           |

TECHNICAL DRAWINGS

