


START Flex Low Output
START Flex IP65 830 2650lm
0068127



Product features

- 5 metre IP65 LED reel with pre-attached 3M adhesive type; equipped with 300 LEDs; 2650lm per 5m (530lm per 1m); 24V; 3000K; CRI80; SDCM 3;Compatible with emergency packs: 0046600, 0046601



PRODUCT OVERVIEW

Product name	START Flex IP65 830 2650lm
Technology	LED
Mount	Other
General application	Hospitality, Retail
ETIM Class	EC002706
E-number FI	4276597
Warranty	5 years
Fixture luminous flux (lm)	2650
Luminaire efficacy (lm/W)	110
Colour temperature (K)	3000
CRI (Ra)	80
Colour Variation Initial (SDCM)	SDCM3
Beam Angle (°)	120
Beam Angle (°)	N/A
Photobiological Risk Group	RG1
Total power consumption (W)	24
Electrical protection	Class III
Dimmable	Yes
Dimming method	Other
Housing colour	Beige
IP rating	IP65
IK rating	IK00
Product EAN number	5410288681276

DATA TABLE

General data	
Product name	START Flex IP65 830 2650lm
Technology	LED
Mount	Other
General application	Hospitality, Retail
Operating temperature range (°C)	-20°C...+40°C

START Flex Low Output

START Flex IP65 830 2650lm
0068127

Performance ambient temperature Tq (°C)	25
ETIM Class	EC002706
E-number FI	4276597
Warranty	5 years

Optical data

Fixture luminous flux (lm)	2650
Luminaire efficacy (lm/W)	110
Colour temperature (K)	3000
CRI (Ra)	80
Colour Variation Initial (SDCM)	SDCM3
Beam Angle (°)	120
Beam Angle (°)	N/A
Photobiological Risk Group	RG1

Electrical data

Total power consumption (W)	24
Electrical protection	Class III
Control gear required	Yes
Dimmable	Yes
Dimming method	Other
Drive current (mA)	1000
Glow Wire Test (°C)	650
Lamp Energy Label (class)	F

Lifetime data

Lifespan L70 B50	54000
Lifespan L70 B10	54000
Lifespan L80 B10	50000
Lifespan L90 B10	44000

Physical data

Housing colour	Beige
IP rating	IP65
IK rating	IK00
Nominal Product Length (mm)	5000
Nominal Product Width (mm)	10
Nominal Product Height (mm)	4
Weight (kg)	0.3

Packaging


Single packaging type	Carton
Product EAN number	5410288681276
Packaging single length / height (cm)	23.5
Packaging single width (cm)	22.5
Packaging single depth (cm)	3.0
DUN14 (outer)	15410288681273
Units per outer package	20

START Flex Low Output
START Flex IP65 830 2650lm
0068127


Packaging outer length / height (cm)	49.0
Packaging outer width (cm)	34.0
Packaging outer depth (cm)	24.0

Safety data	
Optimal operating condition (°C)	-20-40

PHOTOMETRY



TECHNICAL DRAWINGS




START Flex Low Output
START Flex IP65 830 2650lm
0068127



ENERGY
SYLVANIA

0068127




24
kWh/1000h



2019/2015

START Flex Low Output
START Flex IP65 830 2650lm
0068127

 **ENERG** 
SYLVANIA
0068127



24
kWh/1000h

