

START Flex Low Output
START Flex IP65 827 2450lm
0068130



- Product features**
- 5 metre IP65 LED reel with pre-attached 3M adhesive type; equipped with 300 LEDs , 24V; 2700K; CRI80; SDCM 3



PRODUCT OVERVIEW

Product name	START Flex IP65 827 2450lm
Technology	LED
Mount	Other
General application	Hospitality, Retail
ETIM Class	EC002706
E-number FI	4276596
Warranty	5 years
Fixture luminous flux (lm)	2450
Luminaire efficacy (lm/W)	102
Colour temperature (K)	2700
CRI (Ra)	80
Colour Variation Initial (SDCM)	SDCM3
Beam Angle (°)	120
Beam Angle (°)	N/A
Photobiological Risk Group	RG1
Total power consumption (W)	24
Electrical protection	Class III
Dimmable	Yes
Dimming method	Other
Housing colour	Beige
IP rating	IP65
IK rating	IK00
Product EAN number	5410288681306

DATA TABLE

General data	
Product name	START Flex IP65 827 2450lm
Technology	LED
Mount	Other
General application	Hospitality, Retail
Operating temperature range (°C)	-20°C...+40°C
Performance ambient temperature Tq (°C)	25
ETIM Class	EC002706

START Flex Low Output

START Flex IP65 827 2450lm
0068130

E-number FI	4276596
Warranty	5 years

Optical data

Fixture luminous flux (lm)	2450
Luminaire efficacy (lm/W)	102
Colour temperature (K)	2700
CRI (Ra)	80
Colour Variation Initial (SDCM)	SDCM3
Beam Angle (°)	120
Beam Angle (°)	N/A
Photobiological Risk Group	RG1

Electrical data

Total power consumption (W)	24
Electrical protection	Class III
Control gear required	Yes
Dimmable	Yes
Dimming method	Other
Drive current (mA)	1000
Glow Wire Test (°C)	650
Lamp Energy Label (class)	F

Lifetime data

Lifespan L70 B50	54000
Lifespan L70 B10	54000
Lifespan L80 B10	50000
Lifespan L90 B10	44000

Physical data

Housing colour	Beige
IP rating	IP65
IK rating	IK00
Nominal Product Length (mm)	5000
Nominal Product Width (mm)	10
Nominal Product Height (mm)	4
Weight (kg)	0.1

Packaging


Single packaging type	Carton
Product EAN number	5410288681306
Packaging single length / height (cm)	23.5
Packaging single width (cm)	22.5
Packaging single depth (cm)	3.0
DUN14 (outer)	15410288681303
Units per outer package	20
Packaging outer length / height (cm)	49.0
Packaging outer width (cm)	35.0
Packaging outer depth (cm)	24.0

START Flex Low Output
START Flex IP65 827 2450lm
0068130

Safety data

Optimal operating condition (°C)	-20-40
----------------------------------	--------

PHOTOMETRY



TECHNICAL DRAWINGS

START Flex Low Output
START Flex IP65 827 2450lm
0068130



ENERGY
SYLVANIA

0068130




24
kWh/1000h



START Flex Low Output
START Flex IP65 827 2450lm
0068130

 **ENERG** 
SYLVANIA
0068130



24
kWh/1000h

