


Flex Pro Low Output
Flex Pro IP20 2500lm 940
0068169



Product features

- 5 metre IP20 LED reel with pre-attached 3M adhesive type; equipped with 300 LEDs; 2500lm per 5m (500lm per 1m); 24V; 4000K; CRI90; R9>50; SDCM 3;Compatible with emergency packs: 0046600, 0046601



PRODUCT OVERVIEW

Product name	Flex Pro IP20 2500lm 940
Technology	LED
General application	Hospitality
ETIM Class	EC002706
E-number FI	4278332
Warranty	5 years
Fixture luminous flux (lm)	2500
Luminaire efficacy (lm/W)	104
Colour temperature (K)	4000
Light colour	Neutral White
CRI (Ra)	90
Colour Variation Initial (SDCM)	SDCM3
Beam Angle (°)	120
Photobiological Risk Group	RG1
Total power consumption (W)	24
Electrical protection	Class III
Dimmable	Yes
Dimming method	Other
IP rating	IP20
IK rating	IK00
Product EAN number	5410288681696

DATA TABLE

General data	
Product name	Flex Pro IP20 2500lm 940
Technology	LED
General application	Hospitality
Operating temperature range (°C)	-20°C...+40°C
Performance ambient temperature Tq (°C)	25
ETIM Class	EC002706
E-number FI	4278332

Flex Pro Low Output

Flex Pro IP20 2500lm 940
0068169

Warranty 5 years

Optical data

Fixture luminous flux (lm)	2500
Luminaire efficacy (lm/W)	104
Colour temperature (K)	4000
Light colour	Neutral White
CRI (Ra)	90
Colour Variation Initial (SDCM)	SDCM3
Beam Angle (°)	120
Photobiological Risk Group	RG1

Electrical data

Total power consumption (W)	24
Electrical protection	Class III
Control gear required	Yes
Dimmable	Yes
Dimming method	Other
Drive current (mA)	1000
Glow Wire Test (°C)	650
Lamp Energy Label (class)	F

Lifetime data

Lifespan L70 B50	54000
------------------	-------

Physical data

IP rating	IP20
IK rating	IK00
Nominal Product Length (mm)	5000
Nominal Product Width (mm)	8
Nominal Product Height (mm)	1.2
Weight (kg)	0.1

Packaging




Single packaging type	Carton
Product EAN number	5410288681696
Packaging single length / height (cm)	23.5
Packaging single width (cm)	22.5
Packaging single depth (cm)	3.0
DUN14 (outer)	15410288681693
Units per outer package	20
Packaging outer length / height (cm)	49.0
Packaging outer width (cm)	35.0
Packaging outer depth (cm)	24.0

Safety data


Optimal operating condition (°C)	-20-40
----------------------------------	--------

Flex Pro Low Output
Flex Pro IP20 2500lm 940
0068169

PHOTOMETRY



TECHNICAL DRAWINGS




Flex Pro Low Output
Flex Pro IP20 2500lm 940
0068169

**ENERG**

SYLVANIA

0068169




24
kWh/1000h



Flex Pro Low Output
Flex Pro IP20 2500lm 940
0068169

 **ENERG** 
SYLVANIA
0068169



24
kWh/1000h

