

Flex Pro Medium Output
Flex Pro IP20 4750lm 930
0068176



- Product features**
- 5 metre IP20 LED reel with pre-attached 3M adhesive type; equipped with 600 LEDs; 4750lm per 5m (950lm per 1m); 24V; 3000K; CRI90; R9>50; SDCM 3;Compatible with emergency packs: 0046600, 0046601



PRODUCT OVERVIEW

Product name	Flex Pro IP20 4750lm 930
Technology	LED
General application	Hospitality
ETIM Class	EC002706
E-number FI	4278333
Warranty	5 years
Fixture luminous flux (lm)	4750
Luminaire efficacy (lm/W)	99
Colour temperature (K)	3000
Light colour	Warm White
CRI (Ra)	90
Colour Variation Initial (SDCM)	SDCM3
Beam Angle (°)	120
Photobiological Risk Group	RG1
Total power consumption (W)	48
Electrical protection	Class III
Dimmable	Yes
Dimming method	Other
IP rating	IP20
IK rating	IK00
Product EAN number	5410288681764

DATA TABLE

General data	
Product name	Flex Pro IP20 4750lm 930
Technology	LED
General application	Hospitality
Operating temperature range (°C)	-20°C...+40°C
Performance ambient temperature Tq (°C)	25
ETIM Class	EC002706
E-number FI	4278333
Warranty	5 years

Flex Pro Medium Output

Flex Pro IP20 4750lm 930
0068176

Optical data

Fixture luminous flux (lm)	4750
Luminaire efficacy (lm/W)	99
Colour temperature (K)	3000
Light colour	Warm White
CRI (Ra)	90
Colour Variation Initial (SDCM)	SDCM3
Beam Angle (°)	120
Photobiological Risk Group	RG1

Electrical data

Total power consumption (W)	48
Electrical protection	Class III
Control gear required	Yes
Dimmable	Yes
Dimming method	Other
Drive current (mA)	2000
Glow Wire Test (°C)	650
Lamp Energy Label (class)	F
Nominal Frequency (Hz)	N/A

Lifetime data

Lifespan L70 B50	54000
Lifespan L70 B10	54000
Lifespan L80 B10	50000
Lifespan L90 B10	44000

Physical data

IP rating	IP20
IK rating	IK00
Nominal Product Length (mm)	5000
Nominal Product Width (mm)	10
Nominal Product Height (mm)	1.2
Weight (kg)	0.2

Packaging


Single packaging type	Carton
Product EAN number	5410288681764
Packaging single length / height (cm)	23.5
Packaging single width (cm)	22.5
Packaging single depth (cm)	3.0
DUN14 (outer)	15410288681761
Units per outer package	20
Packaging outer length / height (cm)	49.0
Packaging outer width (cm)	35.0
Packaging outer depth (cm)	24.0

Safety data

Optimal operating condition (°C)	-20-40
----------------------------------	--------

Flex Pro Medium Output
Flex Pro IP20 4750lm 930
0068176

PHOTOMETRY



TECHNICAL DRAWINGS



ENERG
SYLVANIA
0068176

A

B

C

D

E

F

G

F

48

kWh/1000h




2019/2015

Flex Pro Medium Output
Flex Pro IP20 4750lm 930
0068176



0068176



48
kWh/1000h

