

Myriad Deco - Housing only

MYRIAD DECO HOUSING FLOOD 3000K PHDM WHITE REF

2057997



- Product features
- The Myriad Housing 3000K Flood accent downlight is a high efficient 10W recessed spotlight, luminous flux: 1037lm, luminaire efficacy 104lm/W. Colour rendering index Ra>80, Colour temperature 3000K, Beam angle 46°, Protection rating IP20, Cut out dimensions: 76mm.

PRODUCT OVERVIEW

|                                 |                                                     |
|---------------------------------|-----------------------------------------------------|
| Product name                    | MYRIAD DECO HOUSING FLOOD 3000K PHDM WHITE REF      |
| Technology                      | LED                                                 |
| Cap/Base                        | N/A                                                 |
| Housing                         | Aluminium                                           |
| Mount                           | Ceiling recessed mounting                           |
| Environment                     | Interior                                            |
| General application             | Hospitality, Office, Residential & Consumer, Retail |
| ETIM Class                      | EC001744                                            |
| Warranty                        | 5 years                                             |
| Fixture luminous flux (lm)      | 1037                                                |
| Luminaire efficacy (lm/W)       | 104                                                 |
| LOR (%)                         | 100                                                 |
| Colour temperature (K)          | 3000                                                |
| Light colour                    | Warm White                                          |
| CRI (Ra)                        | 90                                                  |
| Colour Variation Initial (SDCM) | SDCM3                                               |
| Beam Angle (°)                  | 46                                                  |
| Photobiological Risk Group      | RG1                                                 |
| Total power consumption (W)     | 10                                                  |
| Electrical protection           | Class II                                            |
| Control gear type               | Electronic ballast                                  |
| Dimming method                  | Other                                               |
| Minimum dimming level (%)       | 10                                                  |
| Housing colour                  | White                                               |
| IP rating                       | IP20                                                |
| IK rating                       | IK02                                                |
| Product EAN number              | 5025768579976                                       |

DATA TABLE

|              |                                                |
|--------------|------------------------------------------------|
| General data |                                                |
| Product name | MYRIAD DECO HOUSING FLOOD 3000K PHDM WHITE REF |
| Technology   | LED                                            |
| Cap/Base     | N/A                                            |
| Housing      | Aluminium                                      |
| Mount        | Ceiling recessed mounting                      |

## Myriad Deco - Housing only

*MYRIAD DECO HOUSING FLOOD 3000K PHDM WHITE REF*  
2057997

|                                         |                                                     |
|-----------------------------------------|-----------------------------------------------------|
| Environment                             | Interior                                            |
| General application                     | Hospitality, Office, Residential & Consumer, Retail |
| Performance ambient temperature Tq (°C) | 25                                                  |
| ETIM Class                              | EC001744                                            |
| Warranty                                | 5 years                                             |

### Optical data

|                                 |            |
|---------------------------------|------------|
| Fixture luminous flux (lm)      | 1037       |
| Luminaire efficacy (lm/W)       | 104        |
| LOR (%)                         | 100        |
| Colour temperature (K)          | 3000       |
| Light colour                    | Warm White |
| CRI (Ra)                        | 90         |
| Colour Variation Initial (SDCM) | SDCM3      |
| Adjustable chromaticity         | N          |
| Beam Angle (°)                  | 46         |
| Photobiological Risk Group      | RG1        |

### Electrical data

|                                                          |                    |
|----------------------------------------------------------|--------------------|
| Total power consumption (W)                              | 10                 |
| Primary Supply/Product voltage - min (V)                 | 230                |
| Primary Supply/Product voltage - max (V)                 | 240                |
| Electrical protection                                    | Class II           |
| Control gear type                                        | Electronic ballast |
| Dimming method                                           | Other              |
| Minimum dimming level (%)                                | 10                 |
| Drive current (mA)                                       | 250                |
| Energy Efficiency Class (A->G) of contained light source | E                  |
| Nominal Frequency (Hz)                                   | 50/60Hz            |

### Lifetime data

|                  |        |
|------------------|--------|
| Lifespan L70 B50 | 100000 |
| Lifespan L80 B20 | 100000 |
| Lifespan L90 B10 | 68500  |

### Physical data

|                                                   |       |
|---------------------------------------------------|-------|
| Housing colour                                    | White |
| IP rating                                         | IP20  |
| IK rating                                         | IK02  |
| Nominal Product Height (mm)                       | 72    |
| Cutout Dimensions (W x L in mm or Diameter in mm) | 76    |
| Weight (kg)                                       | 0.39  |
| Recessed Depth (mm)                               | 72    |

### Packaging

|                       |        |
|-----------------------|--------|
| Single packaging type | Carton |
|-----------------------|--------|

## Myriad Deco - Housing only

*MYRIAD DECO HOUSING FLOOD 3000K PHDM WHITE REF*  
**2057997**

|                                       |                |
|---------------------------------------|----------------|
| Product EAN number                    | 5025768579976  |
| Packaging single length / height (cm) | 17.5           |
| Packaging single width (cm)           | 15.0           |
| Packaging single depth (cm)           | 17.5           |
| DUN14 (outer)                         | 05025768579976 |
| Units per outer package               | 1              |
| Packaging outer length / height (cm)  | 17.5           |
| Packaging outer width (cm)            | 15.0           |
| Packaging outer depth (cm)            | 17.5           |

### PHOTOMETRY

---

### TECHNICAL DRAWINGS

---