

Beacon LED XXL - High Output
BEACON XXL WB HO 4K L3 WHT
2059318



Product features

- 2059318 BEACON XXL WB HO 4K L3 WHT Integrated LED spotlight, white RAL 9016, compact and minimalist design, ideal for double height spaces, retail and display applications, die-cast aluminium body, passive cooling heatsink, beam angle: 67° wide beam, optics: Silicone lens for controlled beam, colour temperature: 4000K neutral white, total system power: 48W, total fixture output: 5762lm, luminaire efficacy: 120lm/W, LOR: 100%, colour rendering: Ra 85 typical, LED Chromacity: 3 step MacAdam ellipse, IR/UV free light source without heat radiation, operating voltage: 220-240V / 50-60Hz, drive current: 1200mA, electronic driver, non-dimmable, switched only, power factor: 0.98 electrical protection: CLASS I, 3-circuit track adaptor, suitable for Concord Lytespan 3 track, ingress protection rating: IP20, suitable for internal environment only, horizontal rotation: 355°, vertical tilt: 90°, lockable positioning using Allen key, di...



PRODUCT OVERVIEW

Product name	BEACON XXL WB HO 4K L3 WHT
Technology	LED
Cap/Base	N/A
Housing	Aluminium
Mount	Track mounting
Environment	Internal
General application	Retail
ETIM Class	EC001744
E-number FI	4278875
E-number SE	7401274
Warranty	5 years
Fixture luminous flux (lm)	5762
Luminaire efficacy (lm/W)	120.04
LOR (%)	100
Colour temperature (K)	4000
Light colour	Neutral White
CRI (Ra)	85
Colour Consistency (SDCM)	3
Beam Angle (°)	67
Photobiological Risk Group	RG1
Total power consumption (W)	48
Electrical protection	Class I
Control gear type	Electronic ballast
Dimming method	N/A
Housing colour	White
IP rating	IP20
Product EAN number	5025768593187

DATA TABLE

Beacon LED XXL - High Output

BEACON XXL WB HO 4K L3 WHT

2059318

General data

Product name	BEACON XXL WB HO 4K L3 WHT
Technology	LED
Cap/Base	N/A
Housing	Aluminium
Mount	Track mounting
Environment	Internal
General application	Retail
Performance ambient temperature Tq (°C)	25
ETIM Class	EC001744
E-number FI	4278875
E-number SE	7401274
Warranty	5 years

Optical data

Fixture luminous flux (lm)	5762
Luminaire efficacy (lm/W)	120.04
LOR (%)	100
Colour temperature (K)	4000
Light colour	Neutral White
CRI (Ra)	85
Colour Consistency (SDCM)	3
Adjustable chromaticity	N
Beam Angle (°)	67
Photobiological Risk Group	RG1

Electrical data

Total power consumption (W)	48
Primary Supply/Product voltage - min (V)	220
Primary Supply/Product voltage - max (V)	240
Lamp power factor	0.98
Electrical protection	Class I
Control gear type	Electronic ballast
Dimming method	N/A
Drive current (mA)	1200
Energy Efficiency Class (A->G) of contained light source	D

Lifetime data

Lifespan L70 B50	100000
Lifespan L80 B20	100000
Lifespan L90 B10	55500

Physical data

Housing colour	White
IP rating	IP20
Diffuser finish	Diffuse
Reflector finish	None

Beacon LED XXL - High Output


BEACON XXL WB HO 4K L3 WHT
2059318

Nominal Product Length (mm)	85
Nominal Product Width (mm)	168
Nominal Product Height (mm)	205
Weight (kg)	1.375

Packaging

Single packaging type	Carton
Product EAN number	5025768593187
Packaging single length / height (cm)	25.0
Packaging single width (cm)	19.5
Packaging single depth (cm)	20.0
DUN14 (outer)	05025768593187
Units per outer package	1
Packaging outer length / height (cm)	25.0
Packaging outer width (cm)	19.5
Packaging outer depth (cm)	20.0

PHOTOMETRY



0.5	0.66	E(0°) E(C0)	33.5°	21183 8154
1.0	1.32	E(0°) E(C0)	33.5°	5291 1539
1.5	1.99	E(0°) E(C0)	33.5°	2281 694
2.0	2.65	E(0°) E(C0)	33.5°	1323 395
2.5	3.31	E(0°) E(C0)	33.5°	847 246
3.0	3.97	E(0°) E(C0)	33.5°	588 171

Distance [m] Cone diameter [m]
C0 - C180 (Half beam angle: 67.0°) Illuminance [lx]

TECHNICAL DRAWINGS

