

Equinox LUMINATURE HUMAN CENTRIC LIGHT TUNABLE WHITE (LUMI HCL TW)

EQUINOX 165 1925 LUMI HCL TW SSC BLACK
2059961



Product features

- Equinox LUMI HCL TW is an elegant and innovative luminaire designed using the latest optical technology and Tunable White Human Centric Lighting (2700-6500K) Lumi LED chips (Colour rendering index Ra >97);. It is a high quality and efficient lighting solution for office, hospitality, and retail environments. It creates inspirational halo effects regulated by a unique adjustable optic system. It is Sylsmart dimmable downlight luminaire, For 4000K - Colour rendering index Ra >97; Melanopic Ratio MEER 0.866; Fidelity Index R 95; Gamut Index R 102, Class II, Cut out dimensions: 165mm. Low Glare UGR<19. Finish Jet Black RAL 9005.



PRODUCT OVERVIEW

Product name	EQUINOX 165 1925 LUMI HCL TW SSC BLACK
Technology	LED LumiNature
Cap/Base	N/A
Housing	Aluminium
Mount	Ceiling recessed mounting
General application	Office
ETIM Class	EC001744
Warranty	5 years
Fixture luminous flux (lm)	1925
Luminaire efficacy (lm/W)	77
Colour temperature (K)	4000
Light colour	Tuneable White HCL
CRI (Ra)	97
Colour Variation Initial (SDCM)	SDCM3
Colour Consistency (SDCM)	3
Beam Angle (°)	64
Glare control	< 19
Photobiological Risk Group	RG1
Total power consumption (W)	25
Electrical protection	Class II
Control gear type	LED driver constant current
Control gear mounting	Remote
Dimmable	Yes
Dimming method	SylSmart SSC
Minimum dimming level (%)	1
Housing colour	RAL 9005 - Jet black
IP rating	IP20
IK rating	IK02
Product EAN number	5025768599615

Equinox LUMINATURE HUMAN CENTRIC LIGHT TUNABLE WHITE (LUMI HCL TW)

EQUINOX 165 1925 LUMI HCL TW SSC BLACK
2059961

DATA TABLE

General data

Product name	EQUINOX 165 1925 LUMI HCL TW SSC BLACK
Technology	LED LumiNature
Cap/Base	N/A
Housing	Aluminium
Mount	Ceiling recessed mounting
General application	Office
Operating temperature range (°C)	1°C...+25°C
Performance ambient temperature T _a (°C)	25
ETIM Class	EC001744
Warranty	5 years

Optical data

Fixture luminous flux (lm)	1925
Luminaire efficacy (lm/W)	77
Colour temperature (K)	4000
Light colour	Tuneable White HCL
CRI (Ra)	97
Colour Variation Initial (SDCM)	SDCM3
Colour Consistency (SDCM)	3
Beam Angle (°)	64
Distribution type	Diffuse
Glare control	< 19
Photobiological Risk Group	RG1

Electrical data

Total power consumption (W)	25
Primary Supply/Product voltage - min (V)	220
Primary Supply/Product voltage - max (V)	240
Lamp power factor	0.96
THD (at 230 V, 50 Hz, full load, at 100% dimming level) xx.x %	10
Electrical protection	Class II
Control gear type	LED driver constant current
Control gear mounting	Remote
Dimmable	Yes
Dimming method	SylSmart SSC
Minimum dimming level (%)	1
Drive current (mA)	500
Inrush Current (A)	26.4
Inrush Duration (µs)	224
Glow Wire Test (°C)	650
Energy Efficiency Class (A->G) of contained light source	D
Nominal Frequency (Hz)	50/60Hz
Max. products per 10A C Breaker	16

Equinox LUMINATURE HUMAN CENTRIC LIGHT TUNABLE WHITE (LUMI HCL TW)

EQUINOX 165 1925 LUMI HCL TW SSC BLACK

2059961

Max. products per 13A C Breaker	21
Max. products per 16A C Breaker	26
Max. products per 20A C Breaker	33
Max. products per 10A B Breaker	10
Max. products per 13A B Breaker	13
Max. products per 16A B Breaker	16
Max. products per 20A B Breaker	20
Connectable conductor cross section - Min (mm²)	0.5
Connectable conductor cross section - Max (mm²)	2.5

Lifetime data

Lifespan L70 B50	100000
Lifespan L70 B20	100000
Lifespan L70 B10	100000
Lifespan L80 B50	81000
Lifespan L80 B20	76500
Lifespan L80 B10	74500
Lifespan L90 B50	39500
Lifespan L90 B20	37500
Lifespan L90 B10	36500

Physical data

Housing colour	RAL 9005 - Jet black
IP rating	IP20
IK rating	IK02
Diffuser finish	Other
Diffuser material	PMMA Acrylic
Reflector finish	None
Nominal Product Height (mm)	99
Nominal Product Diameter (mm)	175
Cutout Dimensions (W x L in mm or Diameter in mm)	165
Weight (kg)	1.55

Packaging

Single packaging type	Carton
Product EAN number	5025768599615
Packaging single length / height (cm)	20.0
Packaging single width (cm)	25.0
Packaging single depth (cm)	20.0
DUN14 (outer)	05025768599615
Units per outer package	1
Packaging outer length / height (cm)	20.0
Packaging outer width (cm)	25.0
Packaging outer depth (cm)	20.0

Safety data

Optimal operating condition (°C)	1-25
----------------------------------	------

Equinox LUMINATURE HUMAN CENTRIC LIGHT TUNABLE WHITE (LUMI HCL TW)

EQUINOX 165 1925 LUMI HCL TW SSC BLACK

2059961

TECHNICAL DRAWINGS

